

ANRIN

LEADING WATER

Price list

15.03.24

Linear and point drainage
for load classes **A15** to **F900**
Drainage and edging for
sports facilities

NEW!
DIGITAL
PRICE LIST!

Access your prices
anywhere, at any time.



Export Manager

Markus Bürger

Mobile: +49 (0) 151. 57 12 01 20

Phone: +49 (0) 29 47. 97 81-0

Fax: +49 (0) 29 47. 97 81-50

markus.buerger@anrin.com

Customer Service Team

Telephone: +49 (0) 29 47. 9781 0

info@anrin.com

www.anrin.com









Contents

Designation	Load class and page
ANRIN DRAIN reinforced edge channels	
Channel drainage system ANRIN DRAIN, KE-100 to KE-200 for applications up to class E600	
KF-100 with black ductile-iron edge rail GJS	A - E P. 10
KE-100 with galvanised steel edge rail	A - E P. 12
KE-100 with black cataphoretic dip coated steel edge rail	A - E P. 14
KE-100 with stainless steel edge rail	A - E P. 16
KC-100 with galvanised steel edge rail	A - C P. 18
KE-150 with galvanised steel edge rail	A - E P. 24
KE-150 with stainless steel edge rail	A - E P. 26
KE-200 with galvanised steel edge rail	A - E P. 30
KE-200 with stainless steel edge rail	A - E P. 32
KE-300 with galvanised steel edge rail	A - E P. 35
ANRIN DRAIN heavy duty channels	
Channel drainage system ANRIN DRAIN, SF-100 to SF-300 for applications up to class F900	
SF-100	A - F P. 38
SF-150	A - F P. 40
SF-200	A - F P. 42
SF-300	A - F P. 44
SOLID BLOCK 200	A - F P. 46
ANRIN DRAIN slotted top channels	
Channel drainage system ANRIN DRAIN, Z-100 and Z-150 for applications up to class D400	
Z-100, Z-100 stainless steel	A - C P. 48
Z-150, Z-150 stainless steel	A - D P. 50
ANRIN DRAIN Point inlets, Sump assembly system	
Spot drainage for the load classes C250 and D400 / F900	
ANRIN DRAIN point inlet	A - B P. 54
ANRIN DRAIN Sump assembly system	D - F P. 55
ANRIN SELF drainage channels of polymer concrete	
ANRIN SELF-100, - Slotted top, -ECO, -Mini	A - B P. 57
ANRIN SELF-150, -200	A - C P. 65
ANRIN SELF-GL100	A - C P. 68
ANRIN SELF drainage channels of black polypropylene	
PP-EVO Channels NW 100 black polypropylene	A S. 63
PP Channels NW 100 black polypropylene	A - C S. 64
LC-150 Channels NW 150 PE-HD (polyethylene)	A - C S. 64
ANRIN SELF yard sumps and boot scrapers	
ANRIN SELF comfort boot scrapers	A P. 70
	A P. 71
ANRIN Sport	
Drainage and bordering for sports facilities	
ANRIN SPORT Construction elements made of polymer concrete	P. 73
ANRIN SPORT drainage system 125 (Type A/B/E/F)	P. 75
ANRIN SPORT drainage system 125 (Type C.1/C.2/C.3/C.4)	P. 76
ANRIN SPORT drainage system 125 (Type C.5/C.6/C.7/C.8)	P. 77
ANRIN SPORT drainage system tray channel	P. 78
ANRIN SPORT drainage system tray channel with claw groove	P. 79
ANRIN SPORT drainage system turf edge plate	P. 79
ANRIN SPORT drainage system NW 100/125 synthetic turf	P. 80
ANRIN SPORT clamp stone and clamp rail	P. 81
ANRIN SPORT soft kerbings	P. 82
ANRIN SPORT sand trap channels	P. 84
ANRIN SPORT spot intake	P. 84
ANRIN SPORT cable distribution shaft	P. 85
ANRIN International	P. 02
ANRIN drainage systems overview	P. 04
Load classes and associated road surfaces according to DIN 19580 / EN 1433	P. 05
Channel slope types	P. 06
Channel combinations	P. 07
ANRIN seal set	P. 08
Installation of the channel systems	P. 86
General terms and conditions	P. 87


	System	KE-100	KC-100	KE-150	KE-200	KE-300	KF-100	SF-100	SF-150	SF-200	SF-300	Z-100	Z-150	Point inlet	Sump ass.	SELF	SPORT
Application	House, yard and garden	●	●				●					●	●	●		●	
	Landscape gardening	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
	Pedestrian and cycle paths	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
	Pedestrian zones	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
	School yards	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
	Railway platforms	●	●	●	●	●	●	●	●	●	●	●	●		●		
	Car parks	●	●	●	●	●	●	●	●	●	●	●	●		●		
	Multi-storey Car parks	●	●	●	●	●	●										
	Road edge drainage	●	●	●	●	●	●	●	●	●	●	●	●		●		
	Longitudinal drainage of roads							●	●	●	●						
	Industrial surfaces with heavy traffic	●		●	●	●	●	●	●	●	●				●		
	Ports	●		●	●	●	●	●	●	●	●				●		
	Airports							●	●	●	●				●		
	Container-depots	●		●	●	●	●	●	●	●	●				●		
	Filling stations acc. to Federal Water Act							●	●	●	●						
	Storage and Filling stations, depots acc. FWA							●	●	●	●						
	HGV parks	●		●	●	●	●	●	●	●	●				●		
	Playgrounds	●	●	●	●	●	●					●	●	●	●		●
	Sports facilities	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Channel material	Polymer concrete	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
	Plastic															●	
Channel edge material	Galvanised steel edge rail	●	●	●	●	●											
	Stainless steel edge rail	●		●	●	●											
	Ductile-iron edge rail						●	●	●	●	●			●	●	●	
Load class	Class A15 (Test force 15 kN)	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
	Class B125 (Test force 125 kN)	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
	Class C250 (Test force 250 kN)	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
	Class D400 (Test force 400 kN)	●		●	●	●	●	●	●	●	●	●	●		●		
	Class E600 (Test force 600 kN)	●		●	●	●	●	●	●	●	●				●		
	Class F900 (Test force 900 kN)							●	●	●	●				●		
Nominal width	100 mm	●	●				●	●				●				●	●
	150 mm			●					●				●			●	
	200 mm				●					●						●	
	300 mm					●					●			●	●		
Slope type	Constant invert	●	●	●	●	●	●	●	●	●	●	●	●			●	●
	Stepped invert	●		●	●		●	●	●	●							
	Sloping invert 0.5%	●		●			●	●	●	●		●	●				
Joint technique	Tongue and groove system															●	●
	Unilink-Joint, direction-independent	●	●	●	●	●	●	●	●	●	●	●	●		●	●	
Fastening technique	TwistLock	●	●				●										●
	SnapLock, self-locking			●	●	●											
	RapidLock, self-locking							●	●	●	●				●		

Load classes and associated road surfaces according DIN 19580 / EN 1433


Load class	Area of applications	KE-100	KC-100	KE-150	KE-200	KE-300	KF-100	SF-100	SF-150	SF-200	SF-300	SOLID BLOCK	Z-100	Z-150
A15 Test force 15 kN 	Cycle and pedestrian paths	●	●	●	●	●	●	●	●	●	●	●	●	●
	School yards	●	●	●	●	●	●	●	●	●	●	●	●	●
	Greened areas, landscaping	●	●	●	●	●	●	●	●	●	●	●	●	●
B125 Test force 125 kN 	Pathways, pedestrian zones	●	●	●	●	●	●	●	●	●	●	●	●	●
	Car parks, parking decks	●	●	●	●	●	●	●	●	●	●	●	●	●
	Garage drives, courtyards	●	●	●	●	●	●	●	●	●	●	●	●	●
C250 Test force 250 kN 	Roadside drainage	●	●	●	●	●	●	●	●	●	●	●	●	●
	Slip roads and hard shoulders	●	●	●	●	●	●	●	●	●	●	●	●	●
D400* Test force 400 kN 	Roads	●		●	●	●	●	●	●	●	●	●	●	●
	Car parks, motorway parking	●		●	●	●	●	●	●	●	●	●	●	●
	Pedestrian roads	●		●	●	●	●	●	●	●	●	●	●	●
E600* Test force 600 kN 	Roadways in industrial areas	●		●	●	●	●	●	●	●	●	●		
	Areas with high wheel loads	●		●	●	●	●	●	●	●	●	●		
	Non-public roads	●		●	●	●	●	●	●	●	●	●		
F900* Test force 900 kN 	Special surfaces e.g.							●	●	●	●	●		
	Landing strips							●	●	●	●	●		

Exemplary slope type presentation


Sloping invert 0,5%



Stepped invert



Constant invert





Channel system	KF-100	KE-100	KC-100	KE-200	KE-300	SF-100	SF-150	SF-200	SF-300	SOLID-BLOCK 200	Z-100	Z-150
Sloping invert 0,5%	●	●				●	●	●				
Stepped invert	●	●		●		●	●	●				
Constant invert	●	●	●	●	●	●	●	●	●	●	●	●



Combination of the system elements

With our drainage systems, channel lines can be planned in unliwithed ways. Thanks to the UNILINK joint system, the individual elements can be combined particularly easily and uncomplicatedly.



1. Vertical connection to the pipeline via a channel with pipe socket, at the end or in the middle of the channel string.




2. Installation of a sump unit at the end or in the middle of the channel string.



3. Corner connection with channel element with lateral preforms. Installation possible in the incoming or outgoing leg of the channel string.



4. T-joint with central arrangement of the channel element with preforming for connection option.



The Anrin Seal set comprises a Sealer (2 component permanently elastic sealant on polysulphide basis), a mixing stand including helix and a manual cartridge gun. Special applications are e.g. filling stations and installations for the storage, filling and handling, or for the production, treatment and utilisation of substances hazardous to water. The sealer is part of the joint sealing system with the general technical approval no. Z-74.6-27 and has a Kiwa certification. The rules given in the product data sheets and the general technical approval are to be observed.

Designation	Article no.	Content	Euro/piece
Sealer Cartridge	03209100	450 ml	on request
Primer container	03209200	1000 ml	on request
Processing set	03209300		on request



ANRIN Seal set Dosing and consumption

Channel system	Average consumption in ml. per joint	Sealer requirements / cartridge à 450 ml	Primer requirements / container à 1000 ml
KE-100	21,4 ml	20 Joints	120 Joints
KE-150	65,2 ml	7 Joints	100 Joints
KE-200	73,6 ml	6 Joints	80 Joints
KE-300	104,3 ml	4 Joints	63 Joints
KF-100	21,4 ml	20 Joints	120 Joints
SF-100	50,8 ml	10 Joints	120 Joints
SF-150	66,2 ml	7 Joints	100 Joints
SF-200	79,8 ml	6 Joints	80 Joints
SF-300	110,3 ml	4 Joints	65 Joints

ANRIN



LEADING WATER

ANRIN DRAIN
Reinforced edge channels

KF-100, KE-100,
KC-100, KE-150,
KE-200 and
KE-300

Channel drainage
for the load classes
A15 to E600

ANRIN DRAIN reinforced edge channels KF-100
with black ductile-iron edge rail GJS
with UNILINK joint and TwistLock fastening



Designation	Article	Slope %	Length cm	Width cm	Height cm	Weight kg	Pc. / pal.	€/Pc.
KF-100 Channel No. 0*	01600000	0	100	14.4	15.0	19.4	36	149.80
KF-100 Channel No. 0RV***	01600430	0	100	14.4	15.0	19.6	35	168.50
KF-100 Channel No. 005**/*	01600450	0	50	14.4	15.0	10.5	18	107.30
KF-100 Channel No. 1	01600010	0.5	100	14.4	15.5	19.7	36	149.80
KF-100 Channel No. 2	01600020	0.5	100	14.4	16.0	20.0	36	149.80
KF-100 Channel No. 3	01600030	0.5	100	14.4	16.5	20.3	36	149.80
KF-100 Channel No. 4	01600040	0.5	100	14.4	17.0	20.6	36	149.80
KF-100 Channel No. 5*	01600050	0.5	100	14.4	17.5	20.9	36	149.80
KF-100 Channel No. 6	01600060	0.5	100	14.4	18.0	21.2	36	149.80
KF-100 Channel No. 7	01600070	0.5	100	14.4	18.5	21.5	36	149.80
KF-100 Channel No. 8	01600080	0.5	100	14.4	19.0	21.8	36	149.80
KF-100 Channel No. 9	01600090	0.5	100	14.4	19.5	22.1	36	149.80
KF-100 Channel No. 10*	01600100	0.5	100	14.4	20.0	22.4	36	149.80
KF-100 Channel No. 010*	01601000	0	100	14.4	20.0	22.2	36	149.80
KF-100 Channel No. 010RV***	01601030	0	100	14.4	20.0	23	35	168.50
KF-100 Channel No. 0105**/*	01601050	0	50	14.4	20.0	12.4	18	107.30
KF-100 Rinne Nr. 11	01600110	0.5	100	14.4	20.5	22.9	36	149.80
KF-100 Rinne Nr. 12	01600120	0.5	100	14.4	21.0	23.2	36	149.80
KF-100 Rinne Nr. 13	01600130	0.5	100	14.4	21.5	23.6	36	149.80
KF-100 Rinne Nr. 14	01600140	0.5	100	14.4	22.0	23.9	36	149.80
KF-100 Rinne Nr. 15*	01600150	0.5	100	14.4	22.5	24.3	36	149.80
KF-100 Rinne Nr. 16	01600160	0.5	100	14.4	23.0	24.6	36	149.80
KF-100 Rinne Nr. 17	01600170	0.5	100	14.4	23.5	24.9	36	149.80
KF-100 Rinne Nr. 18	01600180	0.5	100	14.4	24.0	25.3	36	149.80
KF-100 Rinne Nr. 19	01600190	0.5	100	14.4	24.5	25.6	36	149.80
KF-100 Rinne Nr. 20*	01600200	0.5	100	14.4	25.0	26.0	36	149.80
KF-100 Channel No. 020*	01602000	0	100	14.4	25.0	21.5	36	149.80
KF-100 Channel No. 020RV***	01602030	0	100	14.4	25.0	21.7	35	168.50
KF-100 Channel No. 0205**/*	01602050	0	50	14.4	25.0	14.4	18	107.30
KF-100 Rinne Nr. 0100*	01603000	0	100	14.4	10.0	16.8	36	149.80
KF-100 Rinne Nr. 0100RV***	01603030	0	100	14.4	10.0	17	35	168.50

* Channel with mouldings for vertical outlet DA/OD 110

** Channel with sideways perforations for the connection of t-junctions, elbow joints and cross-over joints and vertical outlet

*** Channel with moulded-in Venturi Socket

General type approval:

Load classes:

Slope type:

Joint:

Material:

Nominal width:

Width:

Fastening:

For use in facilities of the storage, filling and handling of water polluting substances.
Approval no. Z-74.4-30

A15, B125, C250, D400¹, E600¹ according DIN 19580 / EN 1433

(¹Exception: Cross-road drainage of busy roads)

Sloping invert 0.5% or Stepped invert or Constant invert

Direction-independent joint system UNILINK®, liquid-tight seal

Polymer concrete, with black ductile-iron edge rail, 8 mm edge width


100 mm

144 mm

TwistLock-fastening

ANRIN DRAIN reinforced edge channels KF-100
with black ductile-iron edge rail GJS
with UNILINK joint and TwistLock fastening

Designation	Article	Lenght cm	Width cm	Height cm	Weight kg	Pc. / Pal.	€uro/ Pc.
KF-100 Sump unit with dirt trap bucket outlets DA/OD 110 and 160 with shaped NBR-rings	01606000	50	14.4	50.0	36.0	9	357.30




Pipe socket HDPE						
DA/OD 110	03206800			0.2		7.00
DA/OD 160	03206810			0.6		22.80



KF-100 Closed end cap with black ductile-iron edge rail and UNILINK-joint						
for channel No. 0	01607050			0.9		33.30
for channel No. 0100	01607900			0.6		33.30
for channel No. 0 - 0105	01607000			1.1		33.30
for channel No. 0 - 0205	01607100			1.2		33.30



KF-100 End cap with pipe socket DA/OD 110 with black ductile-iron edge rail						
for channel No. 0	01608000			1.0		58.90
for channel No. 10,010	01608100			1.2		58.90
for channel No. 20,020	01608200			1.4		58.90





KF-100 End cap with pipe socket DA/OD 50 with black ductile-iron edge rail and UNILINK-joint						
for channel No. 0100	01608900			0.4		58.90



KF-100 Step connector for compensating level differences, height = 5.00 cm						
	01607500			0.5		26.90

All prices are non-binding and do not include the applicable VAT.
We reserve the right to make technical modifications.

ANRIN DRAIN reinforced edge channels KE-100
with galvanised steel edge rail
with UNILINK joint and TwistLock fastening



Designation		Article	Slope %	Lenght cm	Width cm	Height cm	Weight kg	Pc. / Pal.	€uro/ Pc.
KE-100 Channel No.	0*	01100000	0	100	13.6	15.0	17.5	36	104.40
KE-100 Channel No.	0RV***	01100430	0	100	13.6	15.0	17.5	35	123.60
KE-100 Channel No.	005**/*	01100450	0	50	13.6	15.0	9.5	18	75.80
KE-100 Channel No.	1	01100010	0.5	100	13.6	15.5	17.5	36	104.40
KE-100 Channel No.	2	01100020	0.5	100	13.6	16.0	17.5	36	104.40
KE-100 Channel No.	3	01100030	0.5	100	13.6	16.5	18	36	104.40
KE-100 Channel No.	4	01100040	0.5	100	13.6	17.0	18	36	104.40
KE-100 Channel No.	5*	01100050	0.5	100	13.6	17.5	18.5	36	104.40
KE-100 Channel No.	05*	01100500	0	100	13.6	17.5	18.5	36	104.40
KE-100 Channel No.	05RV***	01100530	0	100	13.6	17.5	18.5	35	123.60
KE-100 Channel No.	055**/*	01100550	0	50	13.6	17.5	9.5	18	75.80
KE-100 Channel No.	6	01100060	0.5	100	13.6	18.0	19	36	104.40
KE-100 Channel No.	7	01100070	0.5	100	13.6	18.5	19.5	36	104.40
KE-100 Channel No.	8	01100080	0.5	100	13.6	19.0	19.5	36	104.40
KE-100 Channel No.	9	01100090	0.5	100	13.6	19.5	20	36	104.40
KE-100 Channel No.	10*	01100100	0.5	100	13.6	20.0	21	36	104.40
KE-100 Channel No.	010*	01101000	0	100	13.6	20.0	21	36	104.40
KE-100 Channel No.	010RV***	01101030	0	100	13.6	20.0	21	35	123.60
KE-100 Channel No.	0105**/*	01101050	0	50	13.6	20.0	10.5	18	75.80
KE-100 Channel No.	11	01100110	0.5	100	13.6	20.5	20.5	36	104.40
KE-100 Channel No.	12	01100120	0.5	100	13.6	21.0	21	36	104.40
KE-100 Channel No.	13	01100130	0.5	100	13.6	21.5	21.5	36	104.40
KE-100 Channel No.	14	01100140	0.5	100	13.6	22.0	21.5	36	104.40
KE-100 Channel No.	15*	01100150	0.5	100	13.6	22.5	22.5	36	104.40
KE-100 Channel No.	16	01100160	0.5	100	13.6	23.0	23	36	104.40
KE-100 Channel No.	17	01100170	0.5	100	13.6	23.5	23	36	104.40
KE-100 Channel No.	18	01100180	0.5	100	13.6	24.0	23.5	36	104.40
KE-100 Channel No.	19	01100190	0.5	100	13.6	24.5	24	36	104.40
KE-100 Channel No.	20*	01100200	0.5	100	13.6	25.0	24.5	36	104.40
KE-100 Channel No.	020*	01102000	0	100	13.6	25.0	25.5	36	104.40
KE-100 Channel No.	020RV***	01102030	0	100	13.6	25.0	25.5	35	123.60
KE-100 Channel No.	0205**/*	01102050	0	50	13.6	25.0	11.2	18	75.80
KE-100 Channel No.	060*	01104060	0	100	13.6	6.0	13.1	36	104.40
KE-100 Channel No.	060RV***	01104093	0	100	13.6	6.0	13.1	35	123.60
KE-100 Channel No.	080*	01103080	0	100	13.6	8.0	13.3	36	104.40
KE-100 Channel No.	080RV***	01103093	0	100	13.6	8.0	13.3	35	123.60
KE-100 Channel No.	0100*	01103000	0	100	13.6	10.0	14.4	36	104.40
KE-100 Channel No.	0100RV***	01103013	0	100	13.6	10.0	14.4	35	123.60

* Channel with mouldings for vertical outlet DA/OD 110

** Channel with sidewise perforations for the connection of t-junctions, elbow joints and cross-over joints and vertical outlet

*** Channel with moulded-in Venturi Socket

Load classes:

A15, B125, C250, D400¹, E600¹ according DIN 19580 / EN 1433

(¹Exception: Cross-road drainage of busy roads)

Slope type:

Sloping invert 0.5% or Stepped invert or Constant invert

Joint:

Direction-independent joint system UNILINK®, liquid-tight seal

Material:

Polymer concrete, with galvanised steel edge rails, 6 mm edge width

Nominal width:

100 mm

Width:



136 mm

Fastening:

TwistLock-fastening

ANRIN DRAIN reinforced edge channels KE-100
with galvanised steel edge rail
with UNILINK joint and TwistLock fastening

Designation	Article	Lenght cm	Width cm	Height cm	Weight kg	Pc. / Pal.	€uro/ Pc.
KE-100 Sump unit with dirt trap bucket outlets DA/OD 110 and 160 with shaped NBR-rings	01106000	50	13.6	58.5	38.5	9	273.90
KE-100 Sump unit low height for channels up to No.10 with dirt trap bucket outlets DA/OD 110 and 160 with shaped NBR-rings	01106010	50	13.6	45.0	21.8	9	251.80



Pipe socket					
DA/OD 110	01006800		0.2		7.00
DA/OD 160	01006810		0.6		22.80



KE-100 Closed end cap with galvanised steel edge and UNILINK-joint					
for Channel No. 0-0205	01107000		1.6		27.40
for Channel No. 060	01107400		0.9		27.40
for Channel No. 080	01107800		1.0		27.40
for Channel No. 0100	01107900		1.2		27.40



KE-100 End cap with pipe socket DA/OD 110 with galvanised steel edge and UNILINK-joint					
for Channel No. 0	01108000		1.0		52.50
for Channel No. 5.05	01108050		1.1		52.50
for Channel No. 10,010	01108100		1.2		52.50
for Channel No. 20,020	01108200		1.4		52.50




KE-100 End cap with pipe socket DA/OD 50 with galvanised steel edge and UNILINK-joint					
for Channel No. 080	01108800		0.4		52.50
for Channel No. 0100	01108900		0.4		52.50



KE-100 Step connector for compensating level differences					
	01107500		0.5		28.00

All prices are non-binding and do not include the applicable VAT.
We reserve the right to make technical modifications.

ANRIN DRAIN reinforced edge channels KE-100
with **black cataphoretic dip coated steel edge rail**
with UNILINK joint and TwistLock fastening



Designation	Article	Slope %	Length cm	Width cm	Height cm	Weight kg	Pc. / Pal.	€/Pc.
KE-100 Channel No. 0*	01500000	0	100	13.6	15.0	17.5	36	133.50
KE-100 Channel No. 0RV***	01500430	0	100	13.6	15.0	17.5	35	151.60
KE-100 Channel No. 005**/*	01500450	0	50	13.6	15.0	9.5	18	96.20
KE-100 Channel No. 1	01500010	0.5	100	13.6	15.5	17.5	36	133.50
KE-100 Channel No. 2	01500020	0.5	100	13.6	16.0	17.5	36	133.50
KE-100 Channel No. 3	01500030	0.5	100	13.6	16.5	18	36	133.50
KE-100 Channel No. 4	01500040	0.5	100	13.6	17.0	18	36	133.50
KE-100 Channel No. 5*	01500050	0.5	100	13.6	17.5	18.5	36	133.50
KE-100 Channel No. 05*	01500500	0	100	13.6	17.5	18.5	36	133.50
KE-100 Channel No. 05RV***	01500530	0	100	13.6	17.5	18.5	35	151.60
KE-100 Channel No. 055**/*	01500550	0	50	13.6	17.5	9.5	18	96.20
KE-100 Channel No. 6	01500060	0.5	100	13.6	18.0	19	36	133.50
KE-100 Channel No. 7	01500070	0.5	100	13.6	18.5	19.5	36	133.50
KE-100 Channel No. 8	01500080	0.5	100	13.6	19.0	19.5	36	133.50
KE-100 Channel No. 9	01500090	0.5	100	13.6	19.5	20	36	133.50
KE-100 Channel No. 10*	01500100	0.5	100	13.6	20.0	21	36	133.50
KE-100 Channel No. 010*	01501000	0	100	13.6	20.0	21	36	133.50
KE-100 Channel No. 010RV***	01501030	0	100	13.6	20.0	21	35	151.60
KE-100 Channel No. 0105**/*	01501050	0	50	13.6	20.0	10.5	18	96.20
KE-100 Channel No. 11	01500110	0.5	100	13.6	20.5	20.5	36	133.50
KE-100 Channel No. 12	01500120	0.5	100	13.6	21.0	21	36	133.50
KE-100 Channel No. 13	01500130	0.5	100	13.6	21.5	21.5	36	133.50
KE-100 Channel No. 14	01500140	0.5	100	13.6	22.0	21.5	36	133.50
KE-100 Channel No. 15*	01500150	0.5	100	13.6	22.5	22.5	36	133.50
KE-100 Channel No. 16	01500160	0.5	100	13.6	23.0	23	36	133.50
KE-100 Channel No. 17	01500170	0.5	100	13.6	23.5	23	36	133.50
KE-100 Channel No. 18	01500180	0.5	100	13.6	24.0	23.5	36	133.50
KE-100 Channel No. 19	01500190	0.5	100	13.6	24.5	24	36	133.50
KE-100 Channel No. 20*	01500200	0.5	100	13.6	25.0	24.5	36	133.50
KE-100 Channel No. 020*	01502000	0	100	13.6	25.0	25.5	36	133.50
KE-100 Channel No. 020RV***	01502030	0	100	13.6	25.0	25.5	35	151.60
KE-100 Channel No. 0205**/*	01502050	0	50	13.6	25.0	11.2	18	96.20
KE-100 Channel No. 060*	01504060	0	100	13.6	6.0	13.1	36	133.50
KE-100 Channel No. 060RV***	01504093	0	100	13.6	6.0	13.1	35	151.60
KE-100 Channel No. 080*	01503080	0	100	13.6	8.0	13.3	36	133.50
KE-100 Channel No. 080RV***	01503093	0	100	13.6	8.0	13.3	35	151.60
KE-100 Channel No. 0100*	01503000	0	100	13.6	10.0	14.4	36	133.50
KE-100 Channel No. 0100RV***	01503013	0	100	13.6	10.0	14.4	35	151.60

* Channel with mouldings for vertical outlet DA/OD 110

** Channel with sidewise perforations for the connection of t-junctions, elbow joints and cross-over joints and vertical outlet

*** Channel with moulded-in Venturi Socket

Load classes:

A15, B125, C250, D400¹, E600¹ according DIN 19580 / EN 1433

(¹Exception: Cross-road drainage of busy roads)

Slope type:

Sloping invert 0.5% or Stepped invert or Constant invert

Joint:

Direction-independent joint system UNILINK®, liquid-tight seal

Material:

Polymer concrete, with black cataphoretic dip coated steel edge rail, **6 mm edge width**

Nominal width:

100 mm

Width:



136 mm

Fastening:

TwistLock-fastening

ANRIN DRAIN reinforced edge channels KE-100
with **black cataphoretic dip coated steel edge rail**
with UNILINK joint and TwistLock fastening

Designation	Article	Lenght cm	Width cm	Height cm	Weight kg	Pc. / Pal.	€uro/ Pc.
KE-100 Sump unit with dirt trap bucket outlets DA/OD 110 and 160 with shaped NBR-rings	01506000	50	13.6	58.5	38.5	9	301.90
KE-100 Sump unit low height for channels up to No. 10 with dirt trap bucket outlets DA/OD 110 and 160 with shaped NBR-rings	01506010	50	13.6	45.0	21.8	9	283.30




Pipe socket					
DA/OD 110	01006800		0.2		7.00
DA/OD 160	01006810		0.6		22.80



KE-100 Closed end cap with black galvanised steel edge and UNILINK-joint					
for Channel No. 0-0205	01507000		1.6		33.30
for Channel No. 060	01507400		0.9		33.30
for Channel No. 080	01507800		1.0		33.30
for Channel No. 0100	01507900		1.2		33.30



KE-100 End cap with pipe socket DA/OD 110 with black galvanised steel edge and UNILINK-joint					
for Channel No. 0	01508000		1.0		60.70
for Channel No. 5,05	01508050		1.1		60.70
for Channel No. 10,010	01508100		1.2		60.70
for Channel No. 20,020	01508200		1.4		60.70






KE-100 End cap with pipe socket DA/OD 50 with black galvanised steel edge and UNILINK-joint					
for Channel No. 080	01508800		0.4		60.70
for Channel No. 0100	01508900		0.4		60.70

KE-100 Step connector for compensating level differences					
	01107500		0.5		28.00



All prices are non-binding and do not include the applicable VAT.
We reserve the right to make technical modifications.

ANRIN DRAIN reinforced edge channels KE-100
with stainless steel edge rail
with UNILINK joint and TwistLock fastening



Designation	Article	Slope %	Length cm	Width cm	Height cm	Weight kg	Pc. / Pal.	€/Pc.
KE-100 Channel No. 0*	01400000	0	100	13.6	15.0	17.5	36	232.00
KE-100 Channel No. 0RV***	01400430	0	100	13.6	15.0	17.5	35	250.60
KE-100 Channel No. 005**/*	01400450	0	50	13.6	15.0	9.5	18	166.70
KE-100 Channel No. 1	01400010	0.5	100	13.6	15.5	17.5	36	232.00
KE-100 Channel No. 2	01400020	0.5	100	13.6	16.0	17.5	36	232.00
KE-100 Channel No. 3	01400030	0.5	100	13.6	16.5	18.0	36	232.00
KE-100 Channel No. 4	01400040	0.5	100	13.6	17.0	18.0	36	232.00
KE-100 Channel No. 5*	01400050	0.5	100	13.6	17.5	18.5	36	232.00
KE-100 Channel No. 05*	01400500	0	100	13.6	17.5	18.5	36	232.00
KE-100 Channel No. 05RV***	01400530	0	100	13.6	17.5	18.5	35	250.60
KE-100 Channel No. 055**/*	01400550	0	50	13.6	17.5	9.5	18	166.70
KE-100 Channel No. 6	01400060	0.5	100	13.6	18.0	19.0	36	232.00
KE-100 Channel No. 7	01400070	0.5	100	13.6	18.5	19.5	36	232.00
KE-100 Channel No. 8	01400080	0.5	100	13.6	19.0	19.5	36	232.00
KE-100 Channel No. 9	01400090	0.5	100	13.6	19.5	20.0	36	232.00
KE-100 Channel No. 10*	01400100	0.5	100	13.6	20.0	21.0	36	232.00
KE-100 Channel No. 010*	01401000	0	100	13.6	20.0	21.0	36	232.00
KE-100 Channel No. 010RV***	01401030	0	100	13.6	20.0	21.0	35	250.60
KE-100 Channel No. 0105**/*	01401050	0	50	13.6	20.0	10.5	18	166.70
KE-100 Channel No. 11	01400110	0.5	100	13.6	20.5	20.5	36	232.00
KE-100 Channel No. 12	01400120	0.5	100	13.6	21.0	21.0	36	232.00
KE-100 Channel No. 13	01400130	0.5	100	13.6	21.5	21.5	36	232.00
KE-100 Channel No. 14	01400140	0.5	100	13.6	22.0	21.5	36	232.00
KE-100 Channel No. 15*	01400150	0.5	100	13.6	22.5	22.5	36	232.00
KE-100 Channel No. 16	01400160	0.5	100	13.6	23.0	23.0	36	232.00
KE-100 Channel No. 17	01400170	0.5	100	13.6	23.5	23.0	36	232.00
KE-100 Channel No. 18	01400180	0.5	100	13.6	24.0	23.5	36	232.00
KE-100 Channel No. 19	01400190	0.5	100	13.6	24.5	24.0	36	232.00
KE-100 Channel No. 20*	01400200	0.5	100	13.6	25.0	24.5	36	232.00
KE-100 Channel No. 020*	01402000	0	100	13.6	25.0	25.5	36	232.00
KE-100 Channel No. 020RV***	01402030	0	100	13.6	25.0	25.5	35	250.60
KE-100 Channel No. 0205**/*	01402050	0	50	13.6	25.0	25.5	18	166.70
KE-100 Channel No. 060*	01404060	0	100	13.6	6.0	13.1	36	232.00
KE-100 Channel No. 060RV***	01404093	0	100	13.6	6.0	13.1	35	250.60
KE-100 Channel No. 080*	01403080	0	100	13.6	8.0	13.3	36	232.00
KE-100 Channel No. 080RV***	01403093	0	100	13.6	8.0	13.3	35	250.60
KE-100 Channel No. 0100*	01403000	0	100	13.6	10.0	14.4	36	232.00
KE-100 Channel No. 0100RV***	01403013	0	100	13.6	10.0	14.4	35	250.60

* Channel with mouldings for vertical outlet DA/OD 110

** Channel with sidewise perforations for the connection of t-junctions, elbow joints and cross- over joints and vertical outlet

*** Channel with moulded-in Venturi Socket

Load classes:

A15, B125, C250, D400¹, E600¹ according DIN 19580 / EN 1433

(¹Exception: Cross-road drainage of busy roads)

Slope type:

Sloping invert 0.5% or Stepped invert or Constant invert

Joint:

Direction-independent joint system UNILINK®, liquid-tight seal

Material:

Polymer concrete, with stainless steel edge rail, 6 mm edge width

Nominal width:

100 mm

Width:



136 mm

Fastening:

TwistLock-fastening

ANRIN DRAIN reinforced edge channels KE-100
with stainless steel edge rail
 with UNILINK joint and TwistLock fastening

Designation	Article	Lenght cm	Width cm	Height cm	Weight kg	Pc. / Pal.	€uro/ Pc.
KE-100 Sump unit with dirt trap bucket outlets DN 100 and 160 with shaped NBR-rings	01406000	50	13.6	58.5	38.5	9	384.70
KE-100 Sump unit low height for channels up to No.10 with dirt trap bucket outlets DA/ OD 110 and 160 with shaped NBR-rings	01406010	50	13.6	45.0	21.8	9	359.00



Pipe socket						
DA/OD 110	01006800			0.2		7.00
DA/OD 160	01006810			0.6		22.80



KE-100 Closed end cap with stainless steel edge and UNILINK-joint						
for Channel No. 0-0205	01407000			1.6		58.30
for Channel No. 060	01407400			0.9		58.30
for Channel No. 080	01407800			1.0		58.30
for Channel No. 0100	01407900			1.2		58.30



KE-100 End cap with pipe socket DA/OD 110 with stainless steel edge and UNILINK-joint						
for Channel No. 0	01408000			1.0		85.10
for Channel No. 5,05	01408050			1.1		85.10
for Channel No. 10,010	01408100			1.2		85.10
for Channel No. 20,020	01408200			1.4		85.10



KE-100 End cap with pipe socket DA/OD 50 with stainless steel edge and UNILINK-joint with galvanised steel edge						
for Channel No. 080	01408800			0.4		85.10
for Channel No. 0100	01408900			0.4		85.10



KE-100 Step connector or compensating level differences						
	01107500			0.5		28.00





All prices are non-binding and do not include the applicable VAT.
 We reserve the right to make technical modifications.

ANRIN DRAIN Reinforced edge channels KC-100
with galvanised steel edge rail, 2 mm
with UNILINK-joint and TwistLock-fastening

Designation		Article	Slope %	Lenght cm	Width cm	Height cm	Weight kg	Pc. / Pal.	€uro/ Pc.
KC-100 Channel No.	0*	01800000	0	100	13.0	15.0	12.4	36	92.70
KC-100 Channel No.	0100*	01803000	0	100	13.0	10.0	8.3	36	92.70
KC-100 Rinne Nr.	0RV***	01800330	0	100	13.0	15.0	12.4	36	112.80
KC-100 Rinne Nr.	005	01800450	0	50	13.0	15.0	5.8	36	62.40
KC-100 Rinne Nr.	0100RV***	01803330	0	100	13.0	10.0	8.3	36	112.80

* Channel with mouldings for vertical outlet DA/OD 110

*** Channel with moulded-in Venturi Socket



Load classes:

Slope type:

Joint:

Material:

Nominal width:

Width:

Fastening:

A15, B125, C250 according DIN 19580 / EN 1433

Constant invert

Direction-independent joint system UNILINK®

Polymer concrete, with galvanised edge rail, 2 mm edge width


100 mm

130 mm

TwistLock-fastening

ANRIN DRAIN Reinforced edge channels KC-100
with galvanised steel edge rail, 2 mm
with UNILINK-joint and TwistLock-fastening

Designation	Article	Lenght cm	Width cm	Height cm	Weight kg	Pc. / Pal.	€uro/ Pc.
KC-100 Sump unit with dirt trap bucket Outlets DN 100 and 160 with shaped NBR-rings	01806000	50	13.0	45.0	19.3	9	230.80




Pipe socket				
DA/OD 110	01006800		0.2	7.00
DA/OD 160	01006810		0.6	22.80



KC-100 Closed end cap with galvanised steel edge rail and UNILINK-joint				
for Channel No. 0	01807000		1.6	24.50
for Channel No. 0100	01807900		0.9	24.50



KC-100 End cap with pipe socket DA/OD 110 with galvanised steel edge rail and UNILINK-joint				
for Channel No. 0	01808000			46.10



All prices are non-binding and do not include the applicable VAT.
We reserve the right to make technical modifications.

ANRIN DRAIN reinforced edge channels
KF-100, KE-100 and KC-100 Cover gratings overview



Slotted steel grating, Double slotted steel grating, galvanised, stainless steel,
Load classes: **A15, C250**, Lenght: 50 cm, 100 cm, SW 10 mm



Perforated grating, galvanised, stainless steel
Load classes: **A15, C250**, Lenght: 50 cm, 100 cm, Ø 6 mm



Mesh grating, galvanised, stainless steel
Load classes: **B125, C250, D400**, Lenght: 50 cm, 100 cm
MW 30 x 14 mm / 30 x 10 mm / 20 x 14 mm



Longitudinal profile grating, stainless steel
Load classes: **B125, D400**, Lenght: 50 cm, 100 cm, SW 5 mm



Slotted grating, OvalGrip Design, polyamide, gray
Load class: **B125**, Lenght: 50 cm, SW 8 mm



Slotted grating, OvalGrip Design, polyamide, black
Load class: **C250**, Lenght: 50 cm, SW 8 mm



Slotted grating SW 10,
ductile-iron, cataphoretic dip coating
Load class: **C250**, Lenght: 50 cm, SW 10 mm



Slotted grating, OvalGrip Design,
ductile-iron, cataphoretic dip coating
Load classes: **C250, E600***, Lenght: 50 cm, SW 10 mm

* Exception: Cross-road drainage of busy roads SW = slot width / MW = mesh width

ANRIN DRAIN reinforced edge channels
KF-100, KE-100 and KC-100 Cover gratings overview



Longitudinal-bar grating, ductile-iron, cataphoretic dip coating
Load class: **D400***, Lenght: 50 cm, MW 25 x 10 mm



Design grating, LEAF, ductile-iron, uncoated
Load class: **C250**, Lenght: 50 cm, SW 5 - 9 mm



Design grating, CELTIC, ductile-iron, uncoated
Load class: **C250**, Lenght: 50 cm, SW 10 mm



Slotted grating, HEELGUARD, ductile-iron, coated in black
Load class: **D400***, Lenght: 50 cm, SW 6 mm



Slotted grating, MASSIV 32, ductile-iron, uncoated
Load class: **E600***, Lenght: 50 cm, SW 11 mm
Only suitable for KE-100.



Design grating, WIRE Design, ductile-iron,
cataphoretic dip coating
Load class: **D400***, Lenght: 50 cm, SW 5 mm



Design grating, CIRCLE, GJS ductile-iron, cataphoretic dip coating
Load class: **D400**, Lenght: 50 cm, Ø 19,5 mm



Slotted grating, MASSIV 32, ductile-iron,
cataphoretic dip coating
Load class: **E600***, Lenght: 50 cm, SW 11 mm
Only suitable for KE-100.

* Exception: Cross-road drainage of busy roads SW = slot width / MW = mesh width

All prices are non-binding and do not include the applicable VAT.
We reserve the right to make technical modifications.

Cover gratings with TwistLock
for Reinforced edge channels NW 100

KF-100, KE-100 and KC-100



KF-100, KE-100 and KC-100



KF-100, KE-100 and KC-100



Designation	Article	Lenght cm	Width cm	Inlet Ø cm²/m	Weight kg	Pc. / Pal.	€uro/ Pc.
-------------	---------	--------------	-------------	------------------	--------------	---------------	--------------

Load class A15

Slotted steel grating, galvanised, SW 10 mm	01004200	100	12.3	280	2.4	200	33.30
	01004220	50	12.3	280	1.2	50	29.20
Slotted steel grating, stainless steel, SW 10 mm	01004300	100	12.3	280	2.4	200	148.10
	01004320	50	12.3	280	1.2	50	100.90
Perforated grating, galvanised, Ø 6 mm	01004440	100	12.3	178	1.2	200	32.70
	01004460	50	12.3	178	0.6	50	26.30
Perforated grating, galvanised, Ø 6 mm	01004441	100	12.3	178	1.2	200	148.10
	01004442	50	12.3	178	0.8	50	100.90

Load class B125

Mesh grating, galvanised MW 30 x 14 mm	01004100	100	12.3	870	2.8	200	69.40
	01004120	50	12.3	870	1.5	50	46.10
Longitudinal profile grating, stainless steel, SW 5 mm	01004250	100	12.3	532	4.1	200	308.90
	01004270	50	12.3	532	2.1	50	188.90
Slotted grating, polyamide OvalGrip Design SW 8 mm, color gray	01004140	50	12.3	338	1.1	200	36.20

Load class C250

Double slotted steel grating, galvanised, SW 10 mm	01004600	100	12.3	280	5.0	200	91.50
	01004620	50	12.3	280	2.5	50	61.80
Double slotted steel grating, stainless steel, SW 10 mm	01004640	100	12.3	280	5.0	200	328.10
	01004660	50	12.3	280	2.5	50	218.60
Mesh grating, galvanised MW 30 x 10 mm	01004500	100	12.3	770	4.2	200	97.40
	01004520	50	12.3	770	2.2	50	68.20
Mesh grating, stainless steel MW 20 x 14 mm	01004540	100	12.3	770	4.2	200	503.50
	01004560	50	12.3	770	2.1	50	308.30
Perforated grating, galvanised, Ø 6 mm	01004700	100	12.3	178	4.6	200	137.00
	01004720	50	12.3	178	2.3	50	78.10
Perforated grating, stainless steel, Ø 6 mm	01004740	100	12.3	178	4.9	200	415.60
	01004760	50	12.3	178	2.4	50	217.40
Slotted grating, ductile-iron GJS, cataphoretic dip coating, SW 10 mm	01005021	50	12.3	350	5.8	200	50.70
Slotted grating, ductile-iron GJS, OvalGrip Design, cataphoretic dip coating, SW 10 mm	01005060	50	12.3	420	3.6	200	50.70

Designation	Article	Lenght cm	Width cm	Inlet Ø cm²/m	Weight kg	Pc. / Pal.	€uro/ Pc.
Load class C250							
Slotted grating, polyamide OvalGrip Design, SW 8 mm, color black	01004510	50	12.3	338	1.1	200	46.70
Design grating, LEAF ductile-iron, uncoated, SW 9 mm	01004470	50	12.3	114	4.1	200	114.90
Design grating, CELTIC ductile-iron, uncoated SW 10 mm	01004480	50	12.3	222	3.9	200	114.90
Load class D400¹							
Longitudinal profile grating, stainless steel, SW 5 mm	01004930	100	12.3	505	5.2	200	448.80
	01004931	50	12.3	505	2.6	50	252.40
Mesh grating, galvanised MW 20 x 14 mm	01004900	100	12.3	720	5.2	200	174.90
	01004920	50	12.3	720	2.6	50	117.80
Mesh grating, stainless steel MW 20 x 14 mm	01004940	100	12.3	720	4.2	200	652.70
	01004960	50	12.3	720	2.7	50	416.10
Longitudinal-bar grating, ductile-iron GJS, cataphoretic dip coating, MW 25 x 10 mm	01004970	50	12.3	420	4.1	200	64.70
Slotted grating, HEELGUARD, ductile-iron GJS, coated in black, SW 6 mm	01004980	50	12.3	360	3.8	200	61.80
Slotted grating, HEELGUARD ductile-iron GJS, cataphoretic dip coating, SW 6mm	01004982	50	12,3	360	3,8	200	68.80
Design grating, WIRE, ductile-iron GJS, cataphoretic dip coating, SW 5 mm	01004971	50	12.3	282	3.8	200	68.80
Design grating, CIRCLE, ductile-iron, cataphoretic dip coating, Ø 19,5 mm	01004972	50	12.3	191	4.2	200	68.80
Load class E600¹							
Slotted grating, ductile-iron GJS Oval Grip Design, cataphoretic dip coating, SW 10 mm	01005120	50	12.3	420	5.0	200	73.50
Design grating, MASSIV 32*, ductile-iron GJS, uncoated, SW 11 mm, only suitable for KE-100.	01005130	50	13.5	370	5.8	200	103.80
Design grating, MASSIV 32*, ductile-iron GJS, cataphoretic dip coating, only suitable for KE-100.	01005131	50	13.5	370	5.8	200	103.80
Load class F900¹							
Slotted grating, ductile-iron GJS Oval Grip Design, cataphoretic dip coating, SW 10 mm	01006120	50	12.3	420	5.0	200	82.50

KF-100, KE-100 and KC-100



KF-100, KE-100



KF-100, KE-100




KF-100



¹ Exception: Cross-road drainage of busy roads

ANRIN DRAIN Reinforced edge channels KE-150
with galvanised steel edge rail
with UNILINK-joint and SnapLock-fastening



Designation	Article	Slope %	Length cm	Width cm	Height cm	Weight kg	Pc. / Pal.	€/Pc.
KE-150 Channel No. 0*	01111000	0	100	21.4	22.0	33.0	20	142.20
KE-150 Channel No. 0R***	01111010	0	100	21.4	22.0	33.0		165.60
KE-150 Channel No. 005**/*	01111050	0	50	21.4	22.0	17.9		103.80
KE-150 Channel No. 1*	01110010	0.5	100	21.4	22.5	30.3	15	142.20
KE-150 Channel No. 2*	01110020	0.5	100	21.4	23.0	30.6	15	142.20
KE-150 Channel No. 3*	01110030	0.5	100	21.4	23.5	30.9	15	142.20
KE-150 Channel No. 4*	01110040	0.5	100	21.4	24.0	31.2	15	142.20
KE-150 Channel No. 5*	01110050	0.5	100	21.4	24.5	31.5	15	142.20
KE-150 Channel No. 6*	01110060	0.5	100	21.4	25.0	31.8	15	142.20
KE-150 Channel No. 7*	01110070	0.5	100	21.4	25.5	32.1	15	142.20
KE-150 Channel No. 8*	01110080	0.5	100	21.4	26.0	32.4	15	142.20
KE-150 Channel No. 9*	01110090	0.5	100	21.4	26.5	32.7	15	142.20
KE-150 Channel No. 10*	01110100	0.5	100	21.4	27.0	33.0	15	142.20
KE-150 Channel No. 010*	01112000	0	100	21.4	27.0	35.6	15	142.20
KE-150 Channel No. 010R***	01112010	0	100	21.4	27.0	36.5		165.60
KE-150 Channel No. 0105**/**	01112050	0	50	21.4	27.0	19.0		103.80
KE-150 Channel No. 11*	01110110	0.5	100	21.4	27.5	35.5	15	142.20
KE-150 Channel No. 12*	01110120	0.5	100	21.4	28.0	35.8	15	142.20
KE-150 Channel No. 13*	01110130	0.5	100	21.4	28.5	36.1	15	142.20
KE-150 Channel No. 14*	01110140	0.5	100	21.4	29.0	36.4	15	142.20
KE-150 Channel No. 15*	01110150	0.5	100	21.4	29.5	36.7	15	142.20
KE-150 Channel No. 16*	01110160	0.5	100	21.4	30.0	37.0	15	142.20
KE-150 Channel No. 17*	01110170	0.5	100	21.4	30.5	37.3	15	142.20
KE-150 Channel No. 18*	01110180	0.5	100	21.4	31.0	37.6	15	142.20
KE-150 Channel No. 19*	01110190	0.5	100	21.4	31.5	37.9	15	142.20
KE-150 Channel No. 20*	01110200	0.5	100	21.4	32.0	38.2	15	142.20
KE-150 Channel No. 020*	01113000	0	100	21.4	32.0	38.6	15	142.20
KE-150 Channel No. 020R***	01113010	0	100	21.4	32.0	38.6		165.60
KE-150 Channel No. 0205**/**	01113050	0	50	21.4	32.0	20.9		103.80
KE-150 Channel No. 150P****	01114000	0	100	21.4	13.0	20.1	20	142.20
KE-150 Channel No. 150PR*****	01114050	0	100	21.4	13.0	20.1		165.60
KE-150 Channel No. 0170*	01114100	0	100	21.4	17.0	20.9		142.20

* Channel with mouldings for vertical outlet DA/OD 160

** Channel with sidewise perforations for the connection of t-junctions, elbow joints and cross- over joints and vertical outlet

*** Channel with vertical pipe socket DA/OD 160

**** Channel with mouldings for vertical outlet DA/OD 110

***** Channel with vertical pipe socket DA/OD 110

Optional with black steel edge rail KTL.

Load classes:

A15, B125, C250, D400¹, E600¹ according DIN 19580 / EN 1433

(¹Exception: Cross-road drainage of busy roads)

Slope type:

Sloping invert 0.5% or Stepped invert or Constant invert

Joint:

Direction-independent joint system UNILINK®, liquid-tight seal

Material:

Polymer concrete, with galvanised steel edge rails, 6 mm edge width

Nominal width:

150 mm

Width:


214 mm

Fastening:


SnapLock-fastening

ANRIN DRAIN Reinforced edge channels KE-150
with galvanised steel edge rail
 with UNILINK-joint and SnapLock-fastening

Designation	Article	Lenght cm	Width cm	Height cm	Weight kg	Pc. / Pal.	€uro/ Pc.
KE-150 Sump unit with dirt trap bucket Outlets DA/OD 160 and 200 with shaped NBR-rings	01116000	50	21.4	62.0	54.0	7	469.20



Note:
 ANRIN DRAIN system Sump assembly
 with outlet DA/OD 160, 200
 height 1075 mm and 1475 mm
 see Page 55!



Pipe socket					
DA/OD 110	03206810		0.6		22.80
DA/OD 160	03206820		0.8		56.00



KE-150 Closed end cap with galvanised steel edge and UNILINK-joint					
for Channel No. 0 - 0205	03217000		2.4		35.00
for Channel No. 0	03217050		2.5		35.00
for Channel No. 150P, PR	03217400		1.0		35.00
for Channel No. 0170	03217600		1.2		35.00



KE-150 End cap with pipe socket DA/OD 160 with galvanised steel edge and UNILINK-joint					
for Channel No. 0	03218100		2.3		71.70
for Channel No. 10,010	03218200		3.1		71.70
for Channel No. 20,020	03218300		3.5		71.70
for Channel No. 150P	03218400		0.8		71.70
with pipe socket DA/OD 70					




KE-150 Step connector for compensating level differences					
	03217500		0.5		28.00



Note: Matching end caps with ductile-iron edge can be found in chapter SF-150 on page 40

All prices are non-binding and do not include the applicable VAT.
 We reserve the right to make technical modifications.

ANRIN DRAIN Reinforced edge channels KE-150
with stainless steel edge rail
with UNILINK-joint and SnapLock-fastening



Designation		Article	Slope %	Lenght cm	Width cm	Height cm	Weight kg	Pc. / Pal.	€/Pc.
KE-150 Channel No.	0*	01411000	0	100	21.4	22.0	33.0	20	299.60
KE-150 Channel No.	0R***	01411010	0	100	21.4	22.0	33.0		322.30
KE-150 Channel No.	005**/*	01411050	0	50	21.4	22.0	17.9		215.70
KE-150 Channel No.	1*	01410010	0.5	100	21.4	22.5	30.3	15	299.60
KE-150 Channel No.	2*	01410020	0.5	100	21.4	23.0	30.6	15	299.60
KE-150 Channel No.	3*	01410030	0.5	100	21.4	23.5	30.9	15	299.60
KE-150 Channel No.	4*	01410040	0.5	100	21.4	24.0	31.2	15	299.60
KE-150 Channel No.	5*	01410050	0.5	100	21.4	24.5	31.5	15	299.60
KE-150 Channel No.	6*	01410060	0.5	100	21.4	25.0	31.8	15	299.60
KE-150 Channel No.	7*	01410070	0.5	100	21.4	25.5	32.1	15	299.60
KE-150 Channel No.	8*	01410080	0.5	100	21.4	26.0	32.4	15	299.60
KE-150 Channel No.	9*	01410090	0.5	100	21.4	26.5	32.7	15	299.60
KE-150 Channel No.	10*	01410100	0.5	100	21.4	27.0	33.0	15	299.60
KE-150 Channel No.	010*	01412000	0	100	21.4	27.0	35.6	15	299.60
KE-150 Channel No.	010R***	01412010	0	100	21.4	27.0	35.5		322.30
KE-150 Channel No.	0105**/*	01412050	0	50	21.4	27.0	19.0		215.70
KE-150 Channel No.	11*	01410110	0.5	100	21.4	27.5	35.5	15	299.60
KE-150 Channel No.	12*	01410120	0.5	100	21.4	28.0	35.8	15	299.60
KE-150 Channel No.	13*	01410130	0.5	100	21.4	28.5	36.1	15	299.60
KE-150 Channel No.	14*	01410140	0.5	100	21.4	29.0	36.4	15	299.60
KE-150 Channel No.	15*	01410150	0.5	100	21.4	29.5	36.7	15	299.60
KE-150 Channel No.	16*	01410160	0.5	100	21.4	30.0	37.0	15	299.60
KE-150 Channel No.	17*	01410170	0.5	100	21.4	30.5	37.3	15	299.60
KE-150 Channel No.	18*	01410180	0.5	100	21.4	31.0	37.6	15	299.60
KE-150 Channel No.	19*	01410190	0.5	100	21.4	31.5	37.9	15	299.60
KE-150 Channel No.	20*	01410200	0.5	100	21.4	32.0	38.2	15	299.60
KE-150 Channel No.	020*	01413000	0	100	21.4	32.0	38.6	15	299.60
KE-150 Channel No.	020R***	01413010	0	100	21.4	32.0	38.9		322.30
KE-150 Channel No.	0205**/*	01413050	0	50	21.4	32.0	20.9		215.70
KE-150 Channel No.	150P****	01414000	0	100	21.4	13.0	20.1	20	299.60
KE-150 Channel No.	150PR*****	01414050	0	100	21.4	13.0	20.1	24	322.30
KE-150 Channel No.	0170*	01414100	0	100	21.4	17.0	20.9		299.60

* Channel with mouldings for vertical outlet DA/OD 160

** Channel with sideways perforations for the connection of t-junctions, elbow joints and cross- over joints and vertical outlet

*** Channel with vertical pipe socket DA/OD 160

**** Channel with mouldings for vertical outlet DA/OD 110

***** Channel with vertical pipe socket DA/OD 110

Load classes:

A15, B125, C250, D400¹, E600¹ according DIN 19580 / EN 1433

(¹Exception: Cross-road drainage of busy roads)

Slope type:

Sloping invert 0.5% or Stepped invert or Constant invert

Joint:

Direction-independent joint system UNILINK®, liquid-tight seal

Material:

Polymer concrete, with stainless steel edge rail, 6 mm edge width

Nominal width:

150 mm

Width:

214 mm



Fastening:

SnapLock-fastening

ANRIN DRAIN Reinforced edge channels KE-150
with stainless steel edge rail
 with UNILINK-joint and SnapLock-fastening

Designation	Article	Lenght cm	Width cm	Height cm	Weight kg	Pc. / Pal.	€uro/ Pc.
KE-150 Sump unit with dirt trap bucket Outlets DA/OD 160 and 200 with shaped NBR-rings	01416000	50	21.4	62.0	54.0	7	591.50

Note:
 ANRIN DRAIN system Sump assembly
 with outlet DA/OD 160, 200
 height 1075 mm and 1475 mm
 see Page 55!



Pipe socket						
DA/OD 160	03206810			0.6		22.80
DA/OD 200	03206820			0.8		56.00

KE-150 Closed end cap with stainless steel edge rail and UNILINK-joint						
for Channel No. 0 - 0205	01417000			2.4		63.00
for Channel No. 0	01417050			2.5		63.00
for Channel No. 150P, PR	01417400			1.0		63.00
for Channel No. 0170	01417600			1.2		63.00

KE-150 End cap with Pipe socket DA/OD 160 with stainless steel edge rail and UNILINK-joint						
for Channel No. 0	01418100			1.5		102.00
for Channel No. 10,010	01418200			1.5		102.00
for Channel No. 20,020	01418300			2.0		102.00
for Channel No. 150P	01418400			1.5		102.00
with Pipe socket DA/OD 70						

KE-150 Step connector for compensating level differences						
	03217500			0.5		28.00



All prices are non-binding and do not include the applicable VAT.
 We reserve the right to make technical modifications.

ANRIN DRAIN Reinforced edge channels KE-150
with UNILINK-joint and SnapLock-fastening



Mesh grating, galvanised, stainless
Load classes: **C250**
Lenght: 50 cm, 100 cm, MW 30 x 10 mm



Mesh grating, galvanised, stainless steel
Load classes: **C250, D400***
Lenght: 50 cm, 100 cm, 20 x 20 mm



Longitudinal profile grating, stainless
Load class: **C250**
Lenght: 50 cm, 100 cm, SW 5 mm



Slotted grating with OvalGrip Design, ductile-iron GJS,
cataphoretic dip coating
Load classes: **D400*, E600***
Lenght: 50 cm, SW 12 mm



Longitudinal-bar grating, ductile-iron GJS,
cataphoretic dip coating
Load classes: **D400*, E600***
Lenght: 50 cm, MW 25 x 11 mm



Slotted grating, HEELGUARD, ductile-iron GJS, coated in black
Load class: **D400***
Lenght: 50 cm, SW 6 mm



Design grating, WIRE, ductile-iron GJS,
cataphoretic dip coating
Load class: **D400***
Lenght: 50 cm, SW 5 mm

* Exception: Cross-road drainage of busy roads SW = slot width / MW = mesh width

ANRIN DRAIN Reinforced edge channels KE-150
with UNILINK-joint and SnapLock-fastening

Designation	Article	Length cm	Width cm	Inlet Ø cm²/m	Weight kg	Pc. / Pal.	€uro/ Pc.
-------------	---------	--------------	-------------	------------------	--------------	---------------	--------------

Load class **C250**

Mesh grating galvanised, MW 30 x 10	01114500	100	20.0	1240	9.8	96	317.60
	01114520	50	20.0	1240	4.4	96	226.20
Mesh grating stainless steel, MW 20 x 20	01114540	100	20.0	1240	9.5	96	904.50
	01114560	50	20.0	1240	4.9	96	521.60
Longitudinal profile grating stainless steel, SW 5 mm	01114640	100	20.0	814	9.5	96	838.60
	01114660	50	20.0	814	4.9	96	562.40

Load class **D400¹**

Mesh grating galvanised, MW 20 x 20	01115300	100	20.0	1170	9.8	96	339.20
	01115320	50	20.0	1170	5.0	96	239.00
Mesh grating stainless steel, MW 20 x 20	01115400	100	20.0	1170	9.5	96	963.30
	01115420	50	20.0	1170	4.9	96	721.50
Slotted grating with OvalGrip Design ductile-iron GJS, cataphoretic dip coating, SW 12 mm	01115220	50	20.0	760	7.1	112	110.20
Design grating, WIRE, ductile-iron GJS, cataphoretic dip coating, SW 5 mm	01115630	50	20.0	440	7.0	112	110.20
Longitudinal-bar grating ductile-iron GJS, cataphoretic dip coating, MW 25 x 11 mm	01115620	50	20.0	700	7.8	112	110.20
Slotted grating, HEELGUARD ductile-iron GJS, SW 6 mm	01115230	50	20.0	430	8.0	112	110.20

Load class **E600¹**

Slotted grating with OvalGrip Design ductile-iron GJS, cataphoretic dip coating, SW 12 mm	01115120	50	20.0	760	9.3	112	114.90
Longitudinal-bar grating ductile-iron GJS cataphoretic dip coating, MW 25 x 11 mm	01115520	50	20.0	700	7.8	112	114.90
Access hook, stainless steel for the removal of the cover gratings	01119999						48.00



¹ Exception: Cross-road drainage of busy roads


All prices are non-binding and do not include the applicable VAT.
We reserve the right to make technical modifications.

ANRIN DRAIN Reinforced edge channels KE-200
with galvanised steel edge rail
with UNILINK-joint and SnapLock-fastening

Designation		Article	Slope %	Lenght cm	Width cm	Height cm	Weight kg	Pc. / Pal.	€uro/ Pc.
KE-200 Channel No.	0*	01120000	0	100	26.4	29.0	43.0	9	182.50
KE-200 Channel No.	0R***	01120020	0	100	26.4	29.0	43.0		211.60
KE-200 Channel No.	005**/**	01120050	0	50	26.4	29.0	24.9		132.30
KE-200 Channel No.	010*	01121000	0	100	26.4	34.0	38.0		182.50




- * Channel with mouldings for vertical outlet DA/OD 160
- ** Channel with sidewise perforations for the connection of t-junctions, elbow joints and cross- over joints and vertical outlet
- *** Channel with vertical pipe socket DA/OD 160



KE-200 Channel No.	200P****	01124000	0	100	26.4	13.0	22.2	18	182.50
KE-200 Channel No.	200PR*****	01124010	0	100	26.4	13.0	22.2		211.60
KE-200 Channel No.	0240*	01120240	0	100	26.4	24.0	31.0		182.50
KE-200 Channel No.	0240R	01120242	0	100	26.4	24.0	31.7		211.60

- **** Channel with mouldings for vertical outlet DA/OD 110
- ***** Channel with vertical pipe socket DA/OD 110

Optional with black steel edge rail KTL.



Load classes:

Slope type:

Joint:

Material:

Nominal width:

Width:

Fastening:

A15, B125, C250, D400¹, E600¹ according DIN 19580 / EN 1433

(¹Exception: Cross-road drainage of busy roads)

Constant invert, Stepped invert

Direction-independent joint system UNILINK®, liquid-tight seal

Polymer concrete, with galvanised steel edge rails, 6 mm edge width

200 mm

264 mm



SnapLock-fastening

ANRIN DRAIN Reinforced edge channels KE-200
with galvanised steel edge rail
 with UNILINK-joint and SnapLock-fastening

Designation	Article	Lenght cm	Width cm	Height cm	Weight kg	Pc. / Pal.	€uro/ Pc.
KE-200 Sump unit with galvanised mud bucket and Outlets DA/OD 160 and 200 with shaped NBR-rings	01126000	50	26.4	70.0	59.8	6	545.50



Note:
 ANRIN DRAIN system Sump assembly
 with outlet DA/OD 160, 200
 height 1075 mm and 1475 mm
 see Page 55!



Pipe socket						
DA/OD 160	03206810		0.6			22.80
DA/OD 200	03206820		0.8			56.00



KE-200 Closed end cap with galvanised steel edge and UNILINK-joint						
for Channel No. 0,0240	03227050		3.8			47.30
for Channel No. 200P	03227400		2.8			47.30
for Channel No. 010	03227000					47.30



KE-200 End cap with Pipe socket with galvanised steel edge and UNILINK-joint						
for Channel No. 0 with Pipe socket DA/OD 160	03228000		3.5			77.00
for Channel No. 010 with Pipe socket DA/OD 160	03228100		5.0			77.00
for Channel No. 200P with Pipe socket DA/OD 70	03228500		1.7			77.00




KE-200 Step connector for compensating level differences						
	01207500		0.7			39.10



Note: Matching end caps with ductile-iron edge can be found in chapter SF-200 on page 42

All prices are non-binding and do not include the applicable VAT.
 We reserve the right to make technical modifications.

ANRIN DRAIN Reinforced edge channels KE-200
with stainless steel edge rail
with UNILINK-joint and SnapLock-fastening



Designation		Article	Slope %	Lenght cm	Width cm	Height cm	Weight kg	Pc. / Pal.	€uro/ Pc.
KE-200 Channel No.	0*	01420000	0	100	26.4	29.0	43.0	9	371.80
KE-200 Channel No.	0R***	01420020	0	100	26.4	29.0	43.0		396.90
KE-200 Channel No.	005*/**	01420050	0	50	26.4	29.0	24.9		267.50
KE-200 Channel No.	010*	01421000	0	100	26.4	34.0	38.0		371.80

* Channel with mouldings for vertical outlet DA/OD 160


** Channel with sidewise perforations for the connection of t-junctions, elbow joints and cross- over joints and vertical outlet

*** Channel with vertical pipe socket DA/OD 160

KE-200 Channel No.	200P****	01424000	0	100	26.4	13.0	22.2	18	371.80
KE-200 Channel No.	200PR*****	01424010	0	100	26.4	13.0	22.2		396.90
KE-200 Channel No.	0240*	01420240	0	100	26.4	24.0	31.0		371.80
KE-200 Channel No.	0240R	01420242	0	100	26.4	24.0	31.7		396.90

**** Channel with mouldings for vertical outlet DA/OD 110

***** Channel with vertical pipe socket DA/OD 110



Load classes:

Slope type:

Joint:

Material:

Nominal width:

Width:

Fastening:

A15, B125, C250, D400¹, E600¹ according DIN 19580 / EN 1433

(¹Exception: Cross-road drainage of busy roads)

Constant invert, Stepped invert

Direction-independent joint system UNILINK®, liquid-tight seal

Polymer concrete, with stainless steel edge rail, 6 mm edge width

200 mm

264 mm



SnapLock-fastening

ANRIN DRAIN Reinforced edge channels KE-200
with stainless steel edge rail
 with UNILINK-joint and SnapLock-fastening

Designation	Article	Lenght cm	Width cm	Height cm	Weight kg	Pc. / Pal.	€uro/ Pc.
KE-200 Sump unit with dirt trap bucket and Outlets DA/OD 160 and 200 with shaped NBR-rings	01426000	50	26.4	70.0	59.8	6	639.30



Note:
 ANRIN DRAIN system Sump assembly
 with outlet DA/OD 160, 200
 height 1075 mm and 1475 mm
 see Page 55!



Pipe socket						
DA/OD 160	03206810			0.6		22.80
DA/OD 200	03206820			0.8		56.00



KE-200 Closed end cap with stainless steel edge rail and UNILINK-joint						
for Channel No. 0,0240	01427000			3.8		77.00
for Channel No. 200P	01427400			2.8		77.00
for Channel No. 010	01427010					77.00



KE-200 End cap with Pipe socket DA/OD 160 with stainless steel edge rail and UNILINK-joint						
for Channel No. 0	01428000			3.5		106.70
with Pipe socket DA/OD 160						
for Channel No. 010	01428100			5.0		106.70
with Pipe socket DA/OD 160						
for Channel No. 200P	01428500			1.7		106.70
with Pipe socket DA/OD 70						



KE-200 Step connector for compensating level differences						
	01207500			0.7		39.10



All prices are non-binding and do not include the applicable VAT.
 We reserve the right to make technical modifications.

Cover gratings with SnapLock-fastening
for Reinforced edge channels KE-200



Mesh grating, galvanised, stainless steel
Load classes: **C250**, Length: 50 cm, 100 cm,
MW 30 x 20 mm / 20 x 20 mm



Mesh grating, galvanised, stainless steel
Load classes: **D400***
Length: 50 cm, 100 cm, MW 20 x 20 mm



Slotted grating with OvalGrip Design,
ductile-iron GJS, cataphoretic dip coating
Load classes: **D400***, **E600***, Length: 50 cm, SW 12 mm



Slotted grating, HEELGUARD, ductile-iron GJS,
black coating,
Load classes: **D400***, Length: 50 cm, SW 6 mm

* Exception: Cross-road drainage of busy roads SW = slot width / MW = mesh width

Designation	Article	Lenght cm	Width cm	Inlet Ø cm²/m	Weight kg	Pc. / Pal.	€uro/ Pc.
Load class C250							
Mesh grating galvanised, MW 30 x 20	01124500	100	25.0	1640	10.8	96	367.20
	01124520	50	25.0	1640	5.2	96	258.80
Mesh grating stainless steel, MW 30 x 20	01124540	100	25.0	1640	9.7	96	1198.20
	01124560	50	25.0	1640	5.1	96	837.50
Load class D400¹							
Mesh grating galvanised, MW 20 x 20	01125300	100	25.0	1566	13.8	96	485.50
	01125320	50	25.0	1566	6.8	96	339.20
Mesh grating stainless steel, MW 20 x 20	01125400	100	25.0	1566	12.6	96	1530.90
	01125420	50	25.0	1566	6.5	96	1153.30
Slotted grating with OvalGrip Design ductile-ironn GJS, cataphoretic dip coating, SW 12 mm	01125220	50	25.0	990	11.5	96	166.70
Slotted grating HEELGUARD ductile-iron GJS, coated in black, SW 6 mm	01125230	50	25.0	560	9.3	96	186.50
Load class E600¹							
Slotted grating with OvalGrip Design ductile-iron GJS, cataphoretic dip coating, SW 12 mm	01125120	50	25.0	990	11.9	96	186.50
Access hook, stainless steel for the removal of the cover gratings	01119999						48.00



¹ Exception: Cross-road drainage of busy roads

ANRIN DRAIN Reinforced edge channels KE-300
with galvanised steel edge rail
 with UNILINK-joint and SnapLock-fastening




Designation		Article	Slope %	Lenght cm	Width cm	Height cm	Weight kg	Pc. / Pal.	€/Pc.
KE-300 Channel No.	0	01130000	0	100	36.4	29.0	87.6		287.80
KE-300 Channel No.	0R***	01130010	0	100	36.4	29.0	86.8		317.20
KE-300 Channel with opening Sump assembly top	0SK*	01130060	0	100	36.4	29.0	83.4		339.50
KE-300 Channel No.	020	01132000	0	100	36.4	39.0	98.0		287.80
KE-300 Channel No.	020R***	01132010	0	100	36.4	39.0	97.2		317.20
KE-300 Channel with opening Sump assembly top	020SK*	01132060	0	100	36.4	39.0			339.50
Sump assembly base with connection DA/OD 160, 200 and shaped NBR-rings		03236160		48	33.0	64.5	43.2	5	294.30

* Channel with vertical opening Sump assembly top
 *** Channel with vertical pipe socket DA/OD 160

KE/SF 300 Closed end cap with UNILINK-joint									
KE/SF-300 End cap for Channel No. 0/020		03237010					5.5		75.20
KE/SF 300 End cap with pipe socket DA/OD 160 with UNILINK-joint									
KE/SF-300 End cap for Channel No. 0/020		03238010					9.4		132.30
KE-300 End cap for Channel No. 0R		01138000					9.9		132.30

Optional with stainless steel edge rail or black steel edge rail KTL.



Cover gratings

Designation	Article	Lenght cm	Width cm	Inlet Ø cm²/m	Weight kg	Pc. / Pal.	€/Pc.
Cover gratings cl. D400' with SnapLock-fastening							
Slotted grating with OvalGrip Design ductile-iron GJS, cataphoretic dip coating	01135220	50	35.1		18.0		249.80
Slotted grating with HEELGUARD Design ductile-iron GJS, cataphoretic dip coating	01135240	50	35.1	791	17.9		269.80
Access hook, stainless steel for the removal of the cover gratings	01119999						48.00

Load classes:

Slope type:

Joint:

Material:

Nominal width:

Width:

Fastening:

A15, B125, C250, D400' according DIN 19580 / EN 1433

(*Exception: Cross-road drainage of busy roads)

Constant invert

Direction-independent joint system UNILINK®, liquid-tight seal

Polymer concrete, with galvanized steel edge rail, 6 mm edge width

300 mm

364 mm

SnapLock-fastening

ANRIN



LEADING WATER

ANRIN DRAIN
Heavy duty channels

SF-100, SF-150,
SF-200, SF-300

Channel drainage
for the load classes
D400 to **F900**

ANRIN DRAIN heavy duty channels SF-100
with UNILINK-joint and RapidLock-fastening channels
with black cataphoretic dip coated ductile-iron edge rail, incl. ductile-iron slotted grating cl. F900¹



Designation		Article	Slope %	Length cm	Width cm	Height cm	Weight kg	Pc. / Pal.	€/Pc.
SF-100 Channel No.	0*	03201000	0	100	16.4	16.5	36.0	25	335.70
SF-100 Channel No.	0R***	03201010	0	100	16.4	16.5	36.0	25	357.30
SF-100 Channel No.	005**/*	03201050	0	50	16.4	16.5	19.0	10	207.50
SF-100 Channel No.	1*	03200010	0.5	100	16.4	17.0	36.0	25	335.70
SF-100 Channel No.	2*	03200020	0.5	100	16.4	17.5	36.4	25	335.70
SF-100 Channel No.	3*	03200030	0.5	100	16.4	18.0	36.6	25	335.70
SF-100 Channel No.	4*	03200040	0.5	100	16.4	18.5	36.8	25	335.70
SF-100 Channel No.	5*	03200050	0.5	100	16.4	19.0	37.0	25	335.70
SF-100 Channel No.	6*	03200060	0.5	100	16.4	19.5	37.3	25	335.70
SF-100 Channel No.	7*	03200070	0.5	100	16.4	20.0	37.5	25	335.70
SF-100 Channel No.	8*	03200080	0.5	100	16.4	20.5	38.0	25	335.70
SF-100 Channel No.	9*	03200090	0.5	100	16.4	21.0	38.3	25	335.70
SF-100 Channel No.	10*	03200100	0.5	100	16.4	21.5	38.5	25	335.70
SF-100 Channel No.	010*	03202000	0	100	16.4	21.5	38.5	25	335.70
SF-100 Channel No.	010R***	03202010	0	100	16.4	21.5	38.5	25	357.30
SF-100 Channel No.	0105**/*	03202050	0	50	16.4	21.5	21.0	10	207.50
SF-100 Channel No.	11*	03200110	0.5	100	16.4	22.0	39.0	20	335.70
SF-100 Channel No.	12*	03200120	0.5	100	16.4	22.5	39.3	20	335.70
SF-100 Channel No.	13*	03200130	0.5	100	16.4	23.0	39.8	20	335.70
SF-100 Channel No.	14*	03200140	0.5	100	16.4	23.5	40.5	20	335.70
SF-100 Channel No.	15*	03200150	0.5	100	16.4	24.0	41.0	20	335.70
SF-100 Channel No.	16*	03200160	0.5	100	16.4	24.5	41.4	20	335.70
SF-100 Channel No.	17*	03200170	0.5	100	16.4	25.0	41.6	20	335.70
SF-100 Channel No.	18*	03200180	0.5	100	16.4	25.5	41.7	20	335.70
SF-100 Channel No.	19*	03200190	0.5	100	16.4	26.0	41.9	20	335.70
SF-100 Channel No.	20*	03200200	0.5	100	16.4	26.5	42.0	20	335.70
SF-100 Channel No.	020*	03203000	0	100	16.4	26.5	42.0	20	335.70
SF-100 Channel No.	020R***	03203010	0	100	16.4	26.5	42.0	20	357.30
SF-100 Channel No.	0205**/*	03203050	0	50	16.4	26.5	23.0	10	207.50
SF-100 Channel No.	100-P*	03204000	0	100	16.4	10.0	32.0	25	335.70
SF-100 Channel No.	100-PR***	03204010	0	100	16.4	10.0	32.0	25	357.30

* Channel with mouldings for vertical outlet DA/OD 110

** Channel with sidewise perforations for the connection of t-junctions, elbow joints and cross- over joints and vertical outlet

*** Channel with vertical pipe socket DA/OD 110

General type approval:

Load classes:

Slope type:

Joint:

Nominal width:

Width:

Fastening:

For use in facilities of the storage, filling and handling of water polluting substances.
Approval no. Z-74.4-30

A15, B125, C250, D400¹, E600¹ and F900¹ according DIN 19580 / EN 1433

(*Exception: Cross-road drainage of busy roads)

Sloping invert 0.5% or Stepped invert or Constant invert

UNILINK®-joint

100 mm

164 mm

RapidLock-fastening


ANRIN DRAIN heavy duty channels SF-100
with UNILINK-joint and RapidLock-fastening

with black cataphoretic dip coated ductile-iron edge rail, incl. ductile-iron slotted grating cl. F900¹

Designation	Article	Lenght cm	Width cm	Height cm	Weight kg	Pc. / Pal.	€uro/ Pc.
Sump unit SF-100 incl. ductile-iron grating cl. F900 with RapidLock fastening with mud bucket with DA/OD 110 poured pipe socket and perforations DA/OD 160	03206000	50	16.4	58.5	42.0	9	477.30



Note:
ANRIN DRAIN system Sump assembly
with outlet DA/OD 160, 200
height 1075 mm and 1475 mm
see Page 55!



Step connector					
for compensating level differences	01107500		0.5		28.00

Pipe socket					
DA/OD 110	03206800		0.2		7.00
DA/OD 160	03206810		0.6		22.80

End cap with Unilink joint and ductile-iron edge					
for Channel No. 0 - 0205	03207010		2.4		39.10
for Channel No. 100P	03207510		1.0		39.10

End cap with Pipe socket with Unilink joint and ductile-iron edge with DA/OD 110 poured pipe socket					
for Channel No. 0,005	03208010		1.8		65.90
for Channel No. 10,010	03208110		2.1		65.90
for Channel No. 20,020	03208210		2.5		65.90

for Channel No. 100-P with pipe socket DA/OD 70	03208510		0.6		65.90
--	----------	--	-----	--	-------





¹ Exception: Cross-road drainage of busy roads

All prices are non-binding and do not include the applicable VAT.
We reserve the right to make technical modifications.

ANRIN DRAIN heavy duty channels SF-150
with UNILINK-joint and RapidLock-fastening
with black cataphoretic dip coated ductile-iron edge rail, incl. ductile-iron slotted grating cl. F900¹



SF-150 channel with slotted ductile-iron grating cl. F900¹



Designation		Article	Slope %	Length cm	Width cm	Height cm	Weight kg	Pc. / Pal.	€/Pc.
SF-150 Channel No.	0*	03211000	0	100	21.4	22.0	30.0	20	439.60
SF-150 Channel No.	0R***	03211010	0	100	21.4	22.0	30.0		460.00
SF-150 Channel No.	005**/*	03211050	0	50	21.4	22.0	17.0	8	245.50
SF-150 Channel No.	1*	03210010	0.5	100	21.4	22.5	33.4	16	439.60
SF-150 Channel No.	2*	03210020	0.5	100	21.4	23.0	33.8	16	439.60
SF-150 Channel No.	3*	03210030	0.5	100	21.4	23.5	34.2	16	439.60
SF-150 Channel No.	4*	03210040	0.5	100	21.4	24.0	34.6	16	439.60
SF-150 Channel No.	5*	03210050	0.5	100	21.4	24.5	35.0	16	439.60
SF-150 Channel No.	6*	03210060	0.5	100	21.4	25.0	35.4	16	439.60
SF-150 Channel No.	7*	03210070	0.5	100	21.4	25.5	35.8	16	439.60
SF-150 Channel No.	8*	03210080	0.5	100	21.4	26.0	36.2	16	439.60
SF-150 Channel No.	9*	03210090	0.5	100	21.4	26.5	36.6	16	439.60
SF-150 Channel No.	10*	03210100	0.5	100	21.4	27.0	37.0	16	439.60
SF-150 Channel No.	010*	03212000	0	100	21.4	27.0	37.0	16	439.60
SF-150 Channel No.	010R***	03212010	0	100	21.4	27.0	37.0		460.00
SF-150 Channel No.	0105**/*	03212050	0	50	21.4	27.0	18.8	8	245.50
SF-150 Channel No.	020*	03213000	0	100	21.4	32.0	40.7	12	439.60
SF-150 Channel No.	020R***	03213010	0	100	21.4	32.0	40.7		460.00
SF-150 Channel No.	0205**/*	03213050	0	50	21.4	32.0	20.4	8	245.50

* Channel with mouldings for vertical outlet DA/OD 160

** Channel with sidewise perforations for the connection of t-junctions, elbow joints and cross-over joints

*** Channel with vertical pipe socket DA/OD 160

End cap with Unilink joint and ductile-iron edge									
for Channel No. 0-0205		03217010					2.5		45.50

End cap with Pipe socket DA/OD 160 with Unilink joint and ductile-iron edge with DA/OD 160 poured pipe socket									
for Channel No.	0,005	03218110					2.8		81.10
for Channel No.	10,010	03218210					3.4		81.10
for Channel No.	020	03218310					3.6		81.10

General type approval:

Load classes:

Slope type:

Joint:

Nominal width:

Width:

Fastening:

For use in facilities of the storage, filling and handling of water polluting substances.
Approval no. Z-74.4-30

A15, B125, C250, D400¹, E600¹ and F900¹ according DIN 19580 / EN 1433

(*Exception: Cross-road drainage of busy roads)

Sloping invert 0.5% or Stepped invert or Constant invert

UNILINK®-joint

150 mm

214 mm

RapidLock-fastening


ANRIN DRAIN heavy duty channels SF-150
 with UNILINK-joint and RapidLock-fastening
 with black cataphoretic dip coated ductile-iron edge rail, incl. ductile-iron slotted grating cl. F900¹

Designation	Article	Lenght cm	Width cm	Height cm	Weight kg	Pc. / Pal.	€uro/ Pc.
Sump unit SF-150 with mud bucket with DA/OD 160 poured pipe socket and perforations DA/OD 200	03216000	50	21.4	62.0	55.1	6	653.40



SF-150 sump unit with slotted ductile-iron grating cl. **F900**¹

Note:
 ANRIN DRAIN system Sump assembly
 with outlet DA/OD 160, 200
 height 1075 mm and 1475 mm
 see Page 55!



Step connector						
for compensating level differences	03217500			0.7		28.00

Pipe socket						
DA/OD 160	03206810			0.6		22.80





¹ Exception: Cross-road drainage of busy roads

All prices are non-binding and do not include the applicable VAT.
 We reserve the right to make technical modifications.

ANRIN DRAIN heavy duty channels SF-200
with UNILINK-joint and RapidLock-fastening
with black cataphoretic dip coated ductile-iron edge rail, incl. ductile-iron slotted grating cl. F900¹



SF-200 channel with slotted ductile-iron grating cl. F900¹



SF-200 flat channel with slotted ductile-iron grating cl. F900¹



Designation	Article	Slope %	Length cm	Width cm	Height cm	Weight kg	Pc. / Pal.	€uro/ Pc.
SF-200 Channel No. 0*	03220000	0	100	26.4	29.0	48.2	9	657.50
SF-200 Channel No. 0R***	03220010	0	100	26.4	29.0	48.2		679.70
SF-200 Channel No. 005*/**	03220050	0	50	26.4	29.0	25.6	6	365.50
SF-200 Channel No. 1*	03221010	0.5	100	26.4	29.5	48.2	9	657.50
SF-200 Channel No. 2*	03221020	0.5	100	26.4	30.0	48.8	9	657.50
SF-200 Channel No. 3*	03221030	0.5	100	26.4	30.5	49.4	9	657.50
SF-200 Channel No. 4*	03221040	0.5	100	26.4	31.0	50.0	9	657.50
SF-200 Channel No. 5*	03221050	0.5	100	26.4	31.5	50.6	9	657.50
SF-200 Channel No. 6*	03221060	0.5	100	26.4	32.0	51.2	9	657.50
SF-200 Channel No. 7*	03221070	0.5	100	26.4	32.5	51.8	9	657.50
SF-200 Channel No. 8*	03221080	0.5	100	26.4	33.0	52.4	9	657.50
SF-200 Channel No. 9*	03221090	0.5	100	26.4	33.5	53.0	9	657.50
SF-200 Channel No. 10*	03221100	0.5	100	26.4	34.0	53.6	9	657.50
SF-200 Channel No. 010*	03223000	0	100	26.4	34.0	54.0	9	657.50
SF-200 Channel No. 010R***	03223010	0	100	26.4	34.0	54.0		679.70
SF-200 Channel No. 0105*/**	03223050	0	50	26.4	34.0	29.6	6	365.50
SF-200 Channel No. 200-P****	03225000	0	100	26.4	13.0	30.4	18	657.50
SF-200 Channel No. 200-PR*****	03225010	0	100	26.4	13.0	30.4		679.70

- * Channel with mouldings for vertical outlet DA/OD 160
- ** Channel with sideways perforations for the connection of t-junctions, elbow joints and cross-over joints
- *** Channel with DA/OD 160 poured pipe socket
- **** Channel with mouldings for vertical outlet DA/OD 110
- ***** Channel with vertical pipe socket DA/OD 110

End cap with UNILINK joint and ductile-iron edge

for Channel No. 0 - 010	03227010					2.8		60.10
for Channel No. 200-P	03227410					1.3		60.10

End cap with Pipe socket with UNILINK and ductile-iron edge with poured pipe socket DA/OD 160

for Channel No. 0, 005	03228010					3.6		90.40
for Channel No. 10, 010, 0105	03228110					3.9		90.40
for Channel No. 200-P	03228510					1.3		90.40

General type approval:

Load classes:

Slope type:

Joint:

Nominal width:

Width:

Fastening:

For use in facilities of the storage, filling and handling of water polluting substances.
Approval no. Z-74.4-30

A15, B125, C250, D400¹, E600¹ and F900¹ according DIN 19580 / EN 1433

(*Exception: Cross-road drainage of busy roads)

Sloping invert 0.5% or Stepped invert or Constant invert

UNILINK®-joint

200 mm

264 mm

RapidLock-fastening


ANRIN DRAIN heavy duty channels SF-200
 with UNILINK-joint and RapidLock-fastening
 with black cataphoretic dip coated ductile-iron edge rail, incl. ductile-iron slotted grating cl. F900¹

Designation	Article	Lenght cm	Width cm	Height cm	Weight kg	Pc. / Pal.	€uro/ Pc.
SF-200 Sump unit with mud bucket with DA/OD 160 poured pipe socket and perforations DA/OD 200	03226000	50	26.4	70.0	61.1	6	792.70



SF-200 sump unit with slotted ductile-iron
 grating cl. **F900**¹

Note:
 ANRIN DRAIN system Sump assembly
 with outlet DA/OD 160, 200
 height 1075 mm and 1475 mm
 see Page 55!



Pipe socket						
DA/OD 160	03206810			0.6		22.80
DA/OD 200	03206820			0.8		56.00





¹ Exception: Cross-road drainage of busy roads

All prices are non-binding and do not include the applicable VAT.
 We reserve the right to make technical modifications.

ANRIN DRAIN heavy duty channels SF-300
with UNILINK-joint and RapidLock-fastening
with black cataphoretic dip coated ductile-iron edge rail, incl. ductile-iron slotted grating cl. F900¹



SF-300 channel with slotted ductile-iron grating
cl. **F900¹**



Designation	Article	Slope %	Lenght cm	Width cm	Height cm	Weight kg	Pc. / Pal.	Euro/ Pc.
Rinne SF-300*	03230000		100	36.4	39.0	64.0	6	1095.60
Rinne SF-300R***	03230010		100	36.4	39.0	64.0		1142.30
Rinne SF-300/5*/**	03230050		50	36.4	39.0	35.0	4	724.20
Rinne SF-300P*	03234000		100	36.4	15.0	46.0		1095.60
Rinne SF-300PR***	03234010		100	36.4	15.0	46.0		1142.30

* Channel with mouldings for vertical outlet DA/OD 200

** Channel with sidewise perforations for the connection of t-junctions, elbow joints and cross- over joints and vertical outlet

*** Channel with DA/OD 200 poured pipe socket

End cap with UNILINK joint and ductile-iron edge for all heights								
for Channel SF-300	03237010					5.2		75.20
End cap with Unilink joint and ductile-iron edge								
for Channel SF-300P	03237410					2.4		75.20
End cap with pipe socket with Unilink joint and ductile-iron edge with poured pipe socket DA/OD 200								
for Channel SF-300	03238010					9.1		132.30

General type approval:

Load classes:

Slope type:

Joint:

Nominal width:

Width:

Fastening:

For use in facilities of the storage, filling and handling of water polluting substances.
Approval no. Z-74.4-30

A15, B125, C250, D400¹, E600¹ and F900¹ according DIN 19580 / EN 1433

(*Exception: Cross-road drainage of busy roads)

Constant invert

UNILINK®-joint

300 mm

364 mm


RapidLock-fastening

ANRIN DRAIN heavy duty channels SF-300
with UNILINK-joint and RapidLock-fastening

with black cataphoretic dip coated ductile-iron edge rail, incl. ductile-iron slotted grating cl. F900¹

Designation	Article	Lenght cm	Width cm	Height cm	Weight kg	Pc. / Pal.	€uro/ Pc.
Sump assembly top SF-300 with galvanised mud bucket	03236121	50	36.4	39.0	30.0	4	813.00
Sump assembly raiser for stacking with perforation DA/OD 160	03236140	48	33.0	40.0	24.4	5	125.90
Sump assembly base with connections DA/OD 160, 200 and shaped NBR ring	03236160	48	33.0	64.5	43.2	5	294.30

Attention: The "sump assembly" system element is not intended for use in facilities for the storage, filling and handling of water polluting substances!




Pipe socket					
DA/OD 160	03206810		0.6		22.80
DA/OD 200	03206820		0.8		56.00



¹ Exception: Cross-road drainage of busy roads

All prices are non-binding and do not include the applicable VAT.
We reserve the right to make technical modifications.

ANRIN SOLID BLOCK
from polymer concrete for load classes
D400 to F900




SOLID BLOCK 100 channel element



SOLID BLOCK 200 channel element



SOLID BLOCK 200 sump unit two-piece



Designation	Article	Slope %	Lenght cm	Width cm	Height cm	Weight kg	Pc. / Pal.	€uro/ Pc.
SOLID BLOCK 100 channel element from polymer concrete in monolithic construction	05010000		100	14.8	24.0	33.0		255.30
SOLID BLOCK 100 Access top element from polymer concrete in monolithic construction with ductile-iron slotted grating cl. F900	05010045		65	14.8	24.0	21.8		253.00
SOLID BLOCK 100 Sump units 1-piece from polymer concrete in monolithic construction with ductile-iron slotted grating cl. F900, with dirt trap bucket and perforations DA/OD 110 and 160	05010600		65	14.8	58.5	37.0		464.20
End cap closed	05010700					1.6		48.40
End cap for pipe connection	05010800					1.4		61.20

Designation	Article	Slope %	Lenght cm	Width cm	Height cm	Weight kg	Pc. / Pal.	€uro/ Pc.
SOLID BLOCK 200 channel element from polymer concrete in monolithic construction with EPDM-seal	05300000		100	26.4	32.0	71.5		339.20
SOLID BLOCK 200 Access top element from polymer concrete in monolithic construction, with integrated EPDM-seal, with ductile-iron slotted grating OvalGrip cl. F900	05300450		65	26.4	33.5	38.0		281.50
SOLID BLOCK 200 Sump units 2-piece from polymer concrete in monolithic construction, with integrated EPDM-seal, ductile-iron slotted grating OvalGrip cl. F900, with dirt trap bucket and perforations DA/OD, DA/OD 160 and 200	05306000		65	26.4	69.5	58.8		760.50
End cap closed	05307000			26.4	32.0	4.5		60.10
End cap for pipe connection	05308000			26.4	32.0	3.2		75.10

General type approval:
Load classes:
Slope type:
Joint:
Nominal width:
Width:
Fastening:

Channels are DIBT-accredited for installation in "LAU" systems.
D400 - F900 according DIN 19580 / EN 1433
Constant invert
Tongue and groove system, sealable
200 mm
260 mm
RapidLock-fastening

ANRIN


LEADING WATER

ANRIN DRAIN
Slotted top channels

Slotted top channels Z-100, Z-150

Channel drainage
for decorative
surface design

ANRIN DRAIN slotted top channels Z-100
channels made from polymer concrete with slotted tops made from galvanised steel



Slotted top Z-100 S
with channel Z-100 No. 05



Access top Z-100 S
combined with Channel Z-100 Nr. 055



Access top Z-100 S
with sump unit Z-100



Access hook

Designation	Article	Slope %	Length cm	Width cm	Height cm	Weight kg	Pc. / Pal.	€uro/ Pc.
Z-100 Channel No. 05 from polymer concrete, NW 100 with UNILINK joint	02500500	0	100	13.6	15.3	13.3		61.80
Z-100 Channel No. 055 from polymer concrete, NW 100 with UNILINK joint and perforations for T- and corner butt joints	02500550	0	50	13.6	15.3	7.0		43.20
Z-100 Sump unit with dirt trap bucket, Outlets DA/OD 110 and 160, with shaped NBR-rings	02506010		50	13.6	42.8	26.9		156.20
Z-100 S Slotted top* galvanised, side flush slot, Shaft height = 11 cm	02504511		100	13.6	13.2	5.7		181.30
Z-100 S Slotted top* galvanised, side flush slot, Shaft height = 11 cm	02504551		50	13.6	13.2	2.9		130.00
Z-100 S Access top* galvanised, side flush slot, channel insert for block paving	02504611		50	16.0	13.2	5.0		325.20
Z-100 S Slotted top* galvanised, side flush slot, Shaft height = 16 cm	02504516		100	13.6	18.2	6.9		181.30
Z-100 S Slotted top* galvanised, side flush slot, Shaft height = 16 cm	02504517		50	13.6	18.2	3.5		130.00
Z-100 S Access top* galvanised, side flush slot, channel insert for block paving	02504616		50	16.0	18.2	6.8		325.20
Z-100 End cap closed with galvanised steel edge and UNILINK-joint	01107000					1.6		27.40
Z-100 End cap with pipe socket DA/OD 110 with galvanised steel edge and UNILINK-joint	01108050					1.1		52.50
Access hook pair galvanised steel, for removal of the access top	02509030							58.90

* Shaft heights and slot widths can be varied to match them to an object. Delivery time on request. Channels with sloping invert on request!

Load classes:

Slope type:

Joint:

Inlet cross-section:

Nominal width:

Width:

A15, B125, C250 according DIN 19580 / EN 1433

Constant invert, (Sloping invert 0.5% on request)

Direction-independent joint system UNILINK®, liquid-tight seal


125 cm² / m, slot width SW = 1.25 cm

100 mm

136 mm

ANRIN DRAIN slotted top channels Z-100 stainless steel
channels made from polymer concrete with slotted tops made from stainless steel

Designation	Article	Slope %	Length cm	Width cm	Height cm	Weight kg	Pc. / Pal.	€uro/ Pc.
Z-100 Channel No. 05 from polymer concrete, NW 100 with UNILINK-joint	02500500	0	100	13.6	15.3	13.3		61.80
Z-100 Channel No. 055 from polymer concrete, NW 100 with UNILINK-joint and perforations for T- and corner butt joints	02500550	0	50	13.6	15.3	7.0		43.20
Z-100 Sump unit with dirt trap bucket, Outlets DA/OD 110 and 160, with shaped NBR-rings	02506010		50	13.6	42.8	26.9		156.20
Z-100 S Slotted top* stainless steel, side flush slot, Shaft height = 11 cm	02505511		100	13.6	13.2	5.7		296.70
Z-100 S Slotted top* stainless steel, side flush slot, Shaft height = 11 cm	02505551		50	13.6	13.2	2.9		213.30
Z-100 S Access top* stainless steel, side flush slot, channel insert for block paving	02505611		50	16.0	13.2	5.0		428.40
Z-100 S Slotted top* stainless steel, side flush slot, Shaft height = 16 cm	02505516		100	13.6	18.2	6.9		296.70
Z-100 S Slotted top* stainless steel, side flush slot, Shaft height = 16 cm	02505716		50	13.6	18.2	3.5		213.30
Z-100 S Access top* stainless steel, side flush slot, channel insert for block paving	02505616		50	16	18.2	6.8		428.40
Z-100 End cap closed with stainless steel edge rail and UNILINK-joint	01407000					1.6		58.30
Z-100 End cap with pipe socket DA/OD 110 with stainless steel edge rail and UNILINK-joint	01408050					1.1		85.10
Mesh insert	02509021		100					26.30
Access hook pair galvanised steel, for removal of the access top	02509030							58.90



Slotted top Z-100 S with channel Z-100 No. 05



Access top Z-100 S combined with channel Z-100 Nr. 055



Access top Z-100 S with sump unit Z-100



Mesh insert




Access hook

* Shaft heights and slot widths can be varied to match them to an object. Delivery time on request. Channels with sloping invert on request!

Load classes: **A15, B125, C250** according DIN 19580 / EN 1433
Slope type: Constant invert, (Sloping invert 0.5% on request)
Joint: Direction-independent joint system UNILINK®, liquid-tight seal
Inlet cross-section: 125 cm² / m, slot width SW = 1.25 cm
Nominal width: 100 mm
Width: 136 mm

All prices are non-binding and do not include the applicable VAT.
We reserve the right to make technical modifications.

ANRIN DRAIN slotted top channels Z-150
channels made from polymer concrete with slotted tops made from galvanised steel



Access hook

Designation	Article	Slope %	Length cm	Width cm	Height cm	Weight kg	Pc. / Pal.	€/Pc.
Z-150 Channel No. 0 from polymer concrete, NW 150 with UNILINK joint	02511000	0	100	21.4	18.8	25.8		125.90
Z-150 Channel No. 005 from polymer concrete, NW 150 with UNILINK joint and perforations for T- and corner butt joints	02511050	0	50	21.4	18.8	15.5		81.60
Z-150 Sump unit with dirt trap bucket, Outlets DA/OD 160 and 200, with shaped NBR-rings	02516000		50	21.4	58.8	37.7		304.80
Z-150 S Slotted top* galvanised, side flush slot, Shaft height = 20 cm	02514520		100	21.4	23.0*	8.9		306.00
Z-150 S Access top* galvanised, side flush slot, channel insert for block paving	02514620		50	21.4	23.0*	8.8		530.90
Z-150 Closed end cap with galvanised steel edge and UNILINK-joint	03217000					1.5		35.00
Z-150 End cap with Pipe socket DA/OD 110 with galvanised steel edge and UNILINK-joint	03218100					1.5		71.70
Access hook pair galvanised steel, for removal of the access top	02509030							58.90

* Shaft heights and slot widths can be varied to match them to an object. Delivery time on request. Channels with sloping invert on request!

Load classes:

Slope type:

Joint:

Inlet cross-section:

Nominal width:

Width:

A15, B125, C250, D400¹ according DIN 19580 / EN 1433

(¹Exception: Cross-road drainage of busy roads)

Constant invert, (Sloping invert 0.5% auf request)

Direction-independent joint system UNILINK®, liquid-tight seal

150 cm² / m, slot width SW = 1.5 cm



150 mm

214 mm

ANRIN DRAIN slotted top channels Z-150 stainless steel
channels made from polymer concrete with slotted tops made from stainless steel

Designation	Article	Slope %	Length cm	Width cm	Height cm	Weight kg	Pc. / Pal.	€uro/ Pc.
Z-150 Channel No. 0 from polymer concrete, NW 150 with UNILINK joint	02511000	0	100	21.4	18.8	25.8		125.90
Z-150 Channel No. 005 from polymer concrete, NW 150 with UNILINK joint and perforations for T- and corner butt joints	02511050	0	50	21.4	18.8	15.5		81.60
Z-150 Sump unit with dirt trap bucket, Outlets DA/OD 160 and 200, with shaped NBR-rings	02516000		50	21.4	58.8	37.7		304.80
Z-150 S Slotted top* stainless steel, side flush slot, Shaft height = 20 cm	02515520		100	21.4	23.0*	8.9		602.60
Z-150 S Access top* stainless steel, side flush slot, channel insert for block paving	02515620		50	21.4	23.0*	8.8		726.70
Z-150 Closed end cap with stainless steel edge rail and UNILINK-joint	01417000					1.5		63.00
Z-150 End cap with Pipe socket DA/OD 110 with stainless steel edge rail and UNILINK-joint	01418100					1.5		102.00
Mesh insert	02509021		100					26.30
Access hook pair galvanised steel, for removal of the access top	02509030							58.90

* Shaft heights and slot widths can be varied to match them to an object. Delivery time on request. Channels with sloping invert on request!



Mesh insert



Access hook

Load classes:

A15, B125, C250, D400¹ according DIN 19580 / EN 1433

(¹Exception: Cross-road drainage of busy roads)

Slope type:

Constant invert, (Sloping invert 0.5% on request)

Joint:

Direction-independent joint system UNILINK®, liquid-tight seal

Inlet cross-section:

150 cm² / m, slot width SW = 1.5 cm

Nominal width:

150 mm

Width:

214 mm

All prices are non-binding and do not include the applicable VAT.

We reserve the right to make technical modifications.



ANRIN

LEADING WATER

Point inlets, Sump assembly system

Spot drainage
for the load classes
C250, D400 and **F900**

ANRIN DRAIN point inlet cl. **C250**
with ductile-iron edge rail, including ductile-iron grating



Combination of point inlet with add-on box, with ductile-iron longitudinal-bar grating, plus connections for downpipe and pipe connection.

Designation	Article	Slope %	Lenght cm	Width cm	Height cm	Weight kg	Pc. / Pal.	€uro/ Pc.
Point inlet with ductile-iron edge rail and ductile-iron grating, cl. C250 , as longitudinal-bar grating, with RapidLock fastening with integrated foul air trap, PE mud bucket and premoulded outlet DA/OD 110 with NBR ring	01701200		30	30	40.5	34.7	16	321.70
Point inlet add-on box or increasing the height with formed stand pipe connection DA/OD 110	01706100		30	30	25	10.5		75.20
Pipe socket DA/OD 110 made of PVC	01006800					0.2		7.00

Load classes:
Material:
Fastening:

A15, B125, C250 according EN 124
Inlets from polymer concrete, with ductile-iron frames
RapidLock-fastening


ANRIN DRAIN Sump assembly system
with UNILINK joint and RapidLock fastening inlets made from polymer concrete with black
cataphoretic dip coated ductile-iron edge rail ductile-iron gratings cl. **F900**¹

Designation	Article	Lenght cm	Width cm	Height cm	Weight kg	Pc. / Pal.	€/Pc.
Sump assembly top closed with closed end caps and galvanised mud bucket	03236130	54	36	43	49.0		975.00
Sump assembly top for SF-100 with end caps for the connection with channels SF-100 and galvanised mud bucket	03206120	54	36	43	49.0		975.00
Sump assembly top for KE/SF-150 with end caps for the connection with channels SF-150 or KE-150 and galvanised mud bucket	03216120	54	36	43	49.0		975.00
Sump assembly top for KE/SF-200 with end caps for the connection with channels SF-200 or KE-200 and galvanised mud bucket	03226120	54	36	43	49.0		813.00
Sump assembly raiser for increasing the height with perforation DA/OD 160	03236140	48	33	40	24.4		125.90
Sump assembly base with outlet DA/OD 160. 200 and shaped NBR rings	03236160	48	33	64.5	43.2		294.30

Attention: The "sump assembly" system element is not intended for use in facilities for the storage, filling and handling of water polluting substances!



Sump assembly top with slotted ductile-iron grating cl. **F900**¹



Load classes:

A15, B125, C250, D400¹, F900¹ according DIN 19580 / EN 1433
(¹ Exception: Cross-road drainage of busy roads)

All prices are non-binding and do not include the applicable VAT.
We reserve the right to make technical modifications.

ANRIN

LEADING WATER

SELF- structural elements

Drainage channels,
boot scraper, yard sumps for
the house, yard and garden

ANRIN SELF drainage channels

Channels NW 100 from polymer concrete with grating and locking mechanism



Designation	Article	Lenght cm	Width cm	Height cm	Weight kg	Pc. / Pal.	€uro/ Pc.
SELF-100 Channel 1,0 m with galvanised slotted steel grating HEELGUARD	07821000	100	12.2	9.6	8.3	54	68.80
SELF-100 Channel 1,0 m* with galvanised slotted steel grating HEELGUARD with Venturi Socket	07821100	100	12.2	9.6	8.4	36	78.10
SELF-100 Channel 0,5 m** with galvanised slotted steel grating HEELGUARD	07821050	50	12.2	9.6	4.4	48	47.80
SELF Sump unit H40 with galvanised slotted steel grating HEELGUARD with dirt trap bucket connection DA/OD 110 with sealing ring	07296200	50	12.2	39.6	16.4	12	180.70
SELF-100 Channel 1,0 m with stainless steel grating HEELGUARD	07824000	100	12.2	9.6	8.3	54	165.60
SELF-100 Channel 1,0 m* with stainless steel grating HEELGUARD with Venturi Socket	07824100	100	12.2	9.6	8.4	36	177.20
SELF-100 Channel 0,5 m** with stainless steel grating HEELGUARD	07824050	50	12.2	9.6	4.4	48	107.30
SELF-100 Sump unit H40 with stainless steel grating HEELGUARD with dirt trap bucket connection DA/OD 110 with sealing ring	07296500	50	12.2	39.6	16.4	12	246.00
SELF-100 Channel 1,0 m with stainless steel Longitudinal profile grating	07891000	100	12.2	9.6	9.9	54	312.40
SELF-100 Channel 1,0 m* with stainless steel Longitudinal profile grating with Venturi Socket	07891100	100	12.2	9.6	10.0	36	321.70
SELF-100 Channel 0,5 m** with stainless steel Longitudinal profile grating	07891050	50	12.2	9.6	5.1	48	229.10
SELF-100 Sump unit H40 with stainless steel Longitudinal profile grating with dirt trap bucket connection DA/OD 110 with sealing ring	07796000	50	12.2	39.6	17.2	12	283.30

* Channel 1,0 m with cast in Venturi-socket

** Channel 0,5 m with sidwise perforations for the connection of t-junctions, elbow joints and cross-over joints

Note: Matching accessories can be found on page 62.

Load capacity:

Slope type:

Nominal width:

Width:

Slotted steel grating cl. **A15**, stainless steel-slotted grating cl. **A15**,
stainless steel-longitudinal profile grating cl. **A15**

Constant invert

100 mm

120 mm

ANRIN SELF drainage channels
Channels NW 100 from polymer concrete with grating and locking mechanism

Designation	Article	Lenght cm	Width cm	Height cm	Weight kg	Pc. / Pal.	€uro/ Pc.
SELF-100 Channel 1,0 m with galvanised steel mesh grating	07861000	100	12.2	9.6	9.9	54	102.00
SELF-100 Channel 1,0 m* with galvanised steel mesh grating with Venturi-socket	07861100	100	12.2	9.6	10.0	36	110.20
SELF-100 Channel 0,5 m** with galvanised steel mesh grating	07861050	50	12.2	9.6	5.1	48	73.50
SELF-100 Sump unit H40 with galvanised steel mesh grating with dirt trap bucket connection DA/OD 110 with sealing ring	07696000	50	12.2	39.6	17.2	12	193.50
SELF-100 Channel 1,0 m with slotted grating ductile-iron, OvalGrip	07831000	100	12.2	10.1	12.3	54	99.10
SELF-100 Channel 1,0 m* with slotted grating ductile-iron, OvalGrip with Venturi-socket	07831100	100	12.2	10.1	12.4	36	107.30
SELF-100 Channel 0,5 m** with slotted grating ductile-iron, OvalGrip	07831050	50	12.2	10.1	6.4	48	68.20
SELF-100 Sump unit H40 with slotted grating ductile-iron, OvalGrip with dirt trap bucket, connection DA/OD 110 with sealing ring	07296300	50	12.2	40.1	18.4	12	195.30
SELF-100 Channel 1,0 m with slotted grating polyamide, OvalGrip	07851000	100	12.2	10.3	8.1	54	102.00
SELF-100 Channel 1,0 m* with slotted grating polyamide, OvalGrip with Venturi-socket	07851100	100	12.2	10.3	8.2	36	110.20
SELF-100 Channel 0,5 m** with slotted grating polyamide, OvalGrip	07851050	50	12.2	10.3	4.2	48	71.10
SELF-100 Sump unit H40 with slotted grating polyamide, OvalGrip with dirt trap bucket connection DA/OD 110 with sealing ring	07596000	50	12.2	40.3	16.3	12	202.30

* Channel 1,0 m with cast in Venturi-socket

** Channel 0,5 m with sidewise perforations for the connection of t-junctions, elbow joints and cross-over joints

Note: Matching accessories can be found on page 62.



Load capacity: galvanised Mesh grating cl. **B125**, ductile-iron slotted grating cl. **B125**,
polyamide grating OvalGrip cl. **B125**
Slope type: Constant invert
Nominal width: 100 mm
Width: 120 mm

All prices are non-binding and do not include the applicable VAT.
We reserve the right to make technical modifications.

ANRIN SELF-ECO drainage channels

Channels NW 100 from polymer concrete with grating and locking mechanism



Designation	Article	Lenght cm	Width cm	Height cm	Weight kg	Pc. / Pal.	€uro/ Pc.
SELF-ECO Channel 1,0 m with galvanised slotted steel grating HEELGUARD	07541000	100	12.0	8.0	6.3	54	64.70
SELF-ECO Channel 1,0 m with galvanised slotted steel HEELGUARD with Venturi Socket	07541030	100	12.0	8.0	6.4		72.90
SELF-ECO Channel 0,5 m with galvanised slotted steel grating HEELGUARD	07541050	50	12.0	8.0	3.2	48	44.90
SELF Sump unit NW 100 with galvanised slotted steel HEELGUARD with dirt trap bucket connection DA/OD 110 with sealing ring	07296200	50	12.0	40.0	15.5	12	180.70
SELF-ECO Channel 1,0 m with slotted grating ductile-iron, HEELGUARD	07546000	100	12.0	8.0	10.3	54	91.50
SELF-ECO Channel 1,0 m with slotted grating ductile-iron, HEELGUARD with Venturi Socket	07546030	100	12.0	8.0	6.4		101.20
SELF-ECO Channel 0,5 m with slotted grating ductile-iron, HEELGUARD	07546050	50	12.0	8.0	5.2	48	65.30
SELF Sump unit NW 100 with slotted grating ductile-iron, HEELGUARD with dirt trap bucket connection DA/OD 110 with NBR	07296400	50	12.0	40.0	17.5	12	195.30
SELF-ECO Channel 1,0 m with polyamide grating OvalGrip	07531000	100	12.0	8.0	9.7	54	89.30
SELF-ECO Channel 1,0 m with polyamide grating OvalGrip with Venturi Socket	07531030	100	12.0	8.0	9.9		99.80
SELF-ECO Channel 0,5 m with polyamide grating OvalGrip	07531050	50	12.0	8.0	5.0	48	62.50
SELF Sump unit NW 100 with polyamide grating OvalGrip with dirt trap bucket connection DA/OD 110 with sealing ring	07596000	50	12.0	40.0	16.3	12	202.30
SELF-ECO Channel 1,0 m with ductile-iron slotted grating OvalGrip	07542000	100	12.0	8.0	10.9	54	91.50
SELF-ECO Channel 1,0 m with ductile-iron slotted grating OvalGrip with Venturi Socket	07542030	100	12.0	8.0	10.7		102.10
SELF-ECO Channel 0,5 m with ductile-iron slotted grating OvalGrip	07542050	50	12.0	8.0	5.6	48	65.30
SELF Sump unit NW 100 with ductile-iron slotted grating OvalGrip with dirt trap bucket connection DA/OD 110 with sealing ring	07296300	50	12.0	40.0	18.4	12	195.30

Load capacity:

Slope type:

Nominal width:

Width:

Galvanised slotted grating Heelguard cl. **A15**, ductile-iron slotted grating Heelguard cl. **B125** +
slotted grating polyamide, cl. **B125**

Constant invert

100 mm

120 mm


ANRIN SELF slotted top channels
Channels NW 100 from polymer concrete
combined with slotted top made from galvanised steel with flush side slot

Designation	Article	Length cm	Width cm	Height cm	Weight kg	Pc. / Pal.	€uro/ Pc.
SELF Channel 1,0 m*** incl. SELF slotted top channel galvanised steel, side slit	07484000	100	12.0	19.0	11.3	36	143.40
SELF Channel 0,5 m*** incl. SELF slotted top channel galvanised steel, side slit	07484050	50	12.0	19.0	5.7	36	103.20
SELF Channel 1,0 m*** incl. SELF slotted top channel with Maintenance opening left with Maintenance opening right	07484100	100	12.0	19.0	11.3	36	209.30
	07484200	100	12.0	19.0	11.3	36	209.30
SELF Channel 0,5 m** incl. SELF Revision essay galvanised steel, with side slit insert for block paving	07485000	50	12.0	19.0	8.3	48	185.40
SELF Sump unit with dirt trap bucket connection DA/OD 110 with sealing ring incl. SELF slotted top channel galvanised steel, with side slit insert insert for block paving	07486000	50	12.0	49.0	19.4	12	248.90
Access hook pair galvanised steel, for removal of the revision essays	02509030						58.90

** Channel 0,5 m with sideways perforations for the connection of t-junctions, elbow joints and cross over joints

*** Every 2nd channel with preforming DA/OD 110 for vertical drain

Note: Matching accessories can be found on page 62.



Slotted top channel with lateral inlet
combined with ANRIN SELF Channel



Slotted top channel with maintenance
opening right combined with ANRIN
SELF Channel



Access hook with side inlet,
combined with ANRIN SELF Sump unit



Access hook

Load capacity:
Slope type:

Suitable for car access
Constant invert

All prices are non-binding and do not include the applicable VAT.
We reserve the right to make technical modifications.

ANRIN SELF-MINI drainage channels

Channels NW 100 from polymer concrete with grating and locking mechanism



Designation	Article	Length cm	Width cm	Height cm	Weight kg	Pc. / Pal.	Euro/ Pc.
SELF MINI Channel 1.0 m*** with galvanised slotted grating HEELGUARD	07241000	100	12.0	6.0	6.3	120	64.70
SELF MINI Channel 1.0 m*** with ductile-iron slotted grating, OvalGrip	07362000	100	12.0	6.0	10.5	72	91.50
SELF MINI Channel 1.0 m*** with polyamide slotted grating, OvalGrip	07561000	100	12.0	6.0	10.5	72	89.30

*** Every 2nd channel with perforation DA/OD 110 for vertical outlet

Note: Find matching accessories on page 63.

Load capacity:

Slope type:

Nominal width:

Width:

Fastening:

Slotted steel grating, HEELGUARD, cl. **A15**, ductile-iron slotted grating, OvalGrip, cl. **B125**, polyamide slotted grating OvalGrip cl. **B125**

Constant invert

100 mm

120 mm

Locking mechanism

Designation	Article	Lenght cm	Width cm	Height cm	Weight kg	Pc. / Pal.	€uro/ Pc.
SELF 100 End cap PP made of Polypropylene, grey for SELF Smart SELF ECO SELF Mini	07297200				0.4		11.10
SELF 100 End cap PP made of Polypropylene, grey with pipe connection DA/OD 110 for SELF Smart	07298200				0.8		33.30
SELF 100 End cap PP made of Polypropylene, black for SELF Smart SELF ECO SELF Mini	07297300				0.4		11.10
SELF 100 End cap PP made of Polypropylen, black with pipe connection DA/OD 110 for SELF Smart	07298300				0.8		33.30
SELF ECO End cap made of polymer concrete with pipe socket DA/OD 11	07308100				0.8		33.30



SELF 100 SMART Channel 1,0 m without cover grating	07800001	100	12.0	9.3	6.7		57.20
SELF 100 SMART Rinne 0,5 m without cover grating with sidewise perforations for the con- nection of t-junctions, elbow joints and cross over joint	07800051	50	12.0	9.3	6.8		37.90
SELF 100 SMART Rinne 0,5 m without cover grating with Venturi-socket	07801001	50	12.0	9.3	3.6		68.80
SELF 100 SMART Sump unit H40 without cover grating	07296001	50	12.0	39.0	15.6		174.90
SELF 100 SMART leaf mesh	07809000						5.50
SELF 100 SMART Venturi insert pre-assembled	07809001						6.50



All prices are non-binding and do not include the applicable VAT.
We reserve the right to make technical modifications.

ANRIN drainage channels
Channels NW 100 made of Polypropylen, black



EVO 63 Channel with steel slotted grating cl.A15



EVO 0100 Channel and Sump unit
with polyamide grating
cl.B125



EVO 0150 Channel and Sump unit
with ductile-iron grating OvalGrip
cl.C250



Designation	Article	Lenght cm	Width cm	Height cm	Weight kg	Pc. / Pal.	€uro/ Pc.
PP EVO 063 with slotted steel grating A15	11603000	100	13.1	6.3	2.5	54	61.60
PP EVO 063 with polypropylen grating OvalGrip A15	11602000	100	13.1	6.3	1.6	54	61.60
PP EVO 063 with polyamide grating B125 black	11604000	100	13.1	6.3	2.3	54	98.00
PP EVO 063 with ductile-iron grating OvalGrip C250 black	11605000	100	13.1	6.3	6.8	54	127.10
PP EVO 063 End cap set (DN 100)	11607000						24.50
PP EVO 0100 with slotted steel grating A15	11103000	100	13.1	9.8	2.9	54	61.60
PP EVO 0100 with polypropylene grating A15	11106000	100	13.1	9.8	2.5	54	61.60
PP EVO 0100 with polyamide grating B125 black	11104000	100	13.1	9.8	3.2	54	98.00
PP EVO 0100 with ductile-iron slotted grating OvalGrip C250	11105000	100	13.1	9.8	8.2	54	127.10
PP EVO 0100 Sump unit with slotted steel grating A15	11108030	50	13.1	28.0	1.7		111.80
PP EVO 0100 Sump unit with polypropylene slotted grating A15	11108010	50	13.1	28.0	1.4		111.80
PP EVO 0100 Sump unit with polyamide grating OvalGrip, B125	11108020	50	13.1	28.0	1.5		128.40
PP EVO 0100 Sump unit with ductile-iron slotted grating OvalGrip C250	11108040	50	13.1	28.0	1.8		145.90
PP EVO 0100 End cap Set (DN 110)	11107000		13.1	9.8	0.2		22.80
PP EVO 0150 with slotted steel grating A15	11503000	100	13.1	14.8	3.4	54	65.60
PP EVO 0150 with polypropylene grating A15	11502000	100	13.1	14.8	2.2	54	65.60
PP EVO 0150 with polyamide slotted grating, OvalGrip, B125	11504000	100	13.1	14.8	3.7	54	101.90
PP EVO 0150 with ductile-iron slotted grating OvalGrip C250	11505000	100	13.1	14.8	8.7	54	131.10
PP EVO 0150 Sump unit with slotted steel grating A15	11508030	50	13.1	28.0	1.8		111.80
PP EVO 0150 Sump unit with polypropylene slotted grating A15	11508010	50	13.1	28.0	1.3		111.80
PP EVO 0150 Sump unit with polyamid grating, OvalGrip B125 black	11508020	50	13.1	28.0	1.7		128.40
PP EVO 0150 Sump unit with ductile-iron slottedgrating OvalGrip C250 black	11508040	50	13.1	28.0	3.9		145.90
PP EVO 0150 End cap set (DN 110)	11507000		13.1	14.8	0.2		24.50

Load capacity:

Nominal width:

Fastening:

slotted steel grating cl. **A15**, ductile-iron slotted grating cl. **B125**, polyamide slotted grating,
OvalGrip cl. **B125**

100 mm

Locking mechanism (PP), TwistLock-fastening (EVO)

ANRIN drainage channels
Channels NW 150 made of black polyethylen
PE-HD (Polyethylen)

Designation	Article	Lenght cm	Width cm	Height cm	Weight kg	Pc. / Pal.	€uro/ Pc.
LC-150 090 with polypropylene slotted grating A15	15109000	100	22.5	9	4.6	54	131.10
LC-150 090 with steel mesh grating B125	15109100	100	22.5	9	7.4	54	184.00
LC-150 090 with ductile-iron slotted grating HEELGUARD C250	15109200	100	22.5	9	19.5	54	164.20
LC-150 090 End cap set	15109700						31.80
LC-150 125 with polypropylene slotted grating A15	15112500	100	22.5	12.5	4.8	50	131.10
LC-150 125 with steel mesh grating B125	15112510	100	22.5	12.5	7.6	50	184.00
LC-150 125 with ductile-iron slotted grating HEELGUARD C250	15112520	100	22.5	12.5	19.7	50	164.20
LC-150 125 End cap set	15112570						31.80
LC-150 150 with polypropylene slotted grating A15	15120000	100	22.5	20	5.9	50	141.00
LC-150 150 with steel mesh grating B125	15120010	100	22.5	20	8.7	50	193.90
LC-150 150 with ductile-iron slotted grating HEELGUARD C250	15120020	100	22.5	20	20.8	50	174.10
LC-150 150 End cap set	15120070						33.20



Designation	Article	Lenght cm	Width cm	Height cm	Weight kg	Pc. / Pal.	€uro/ Pc.
PP Channel 080 with polypropylene slotted grating A15	11081000	100	12.1	8.4	1.6	54	64.70
PP Channel 080 with galvanised slotted steel grating A15	11082000	100	12.1	8.4	1.6	54	64.70
PP End cap 080 for galvanised channel claw groove and -spring	11087700						23.40
PP adapter with screws for connection with pipe connections DN 100	11088700						10.00



Load capacity:
Nominal width:
Fastening:

cl. **A15**, **B125** and cl. **C250**
150 mm
locking bridge

All prices are non-binding and do not include the applicable VAT.
We reserve the right to make technical modifications.

ANRIN SELF-150 drainage channels
from polymer concrete with galvanised mesh grating, slotted grating
or slotted ductile-iron grating

Channels only!

Designation	Article	Lenght cm	Width cm	Height cm	Weight kg	Pc. / Pal.	€uro/ Pc.
SELF-150 Channel 1,0 m incl. locking, with perforation DA/OD 160 for vertical outlet	07311001	100	20.0	15.0	14.8	55	92.70
SELF-150 Channel 0,5 m incl. locking, with perforation DA/OD 160 for vertical outlet	07311051	50	20.0	15.0	7.1		68.80
SELF-150P Channel 1,0 m incl. locking, with perforation DA/OD 160 for vertical outlet	07314001	100	20.0	8.0	11.5		92.70
SELF-150 Sump unit incl. locking, with perforation DA/OD 160 for vertical outlet	07316001	50	20.0	58.5	37.6		174.90
SELF-150 End cap for Channel start and -end	07317100				0.5		26.90
SELF-150 End cap with pipe socket DA/OD 160 for Channel end	07318100				1.0		54.20
Pipe connection DA/OD 160	01006810				0.2		22.80



Load capacity:
Slope type:
Nominal width:
Width:
Fastening:

galvanised slotted grating cl. **A15**, mesh grating cl. **B125**, ductile-iron slotted grating cl. **C250**
Constant invert
150 mm
200 mm
Screw-fastening

ANRIN SELF-150 drainage channels
from polymer concrete with galvanised mesh grating, slotted grating
or slotted ductile-iron grating

Cover gratings for SELF-150

Designation	Article	Length cm	Width cm	Height cm	Weight kg	Pc. / Pal.	€uro/ Pc.
SELF-150 galvanised steel slotted grating cl. A15	07313500	100	20.0	471	2.9		44.90
SELF-150 galvanised steel slotted grating cl. A15	07313520	50	20.0	471	1.5		33.80
SELF-150 Steel mesh grating, galvanised, cl. B125, MW 30 x 10 mm	07314500	100	20.0	1033	5.1		99.50
SELF-150 Steel mesh grating, galvanised, cl. B125, MW 30 x 10 mm	07314520	50	20.0	1033	2.6		80.50
SELF-150 Steel mesh grating, galvanised, cl. B125, MW 33 x 33 mm	07314600	100	20.0	1068	4.2		107.90
SELF-150 steel mesh grating, galvanised, cl. B125, MW 33 x 33 mm	07314620	50	20.0	1068	2.1		74.60
SELF-150 Slotted grating, ductile-iron GJS, coated in black, cl. C250	07315500	50	20.0	584	5.3		60.70



Load capacity: galvanised slotted grating cl. **A15**, mesh grating cl. **B125**, ductile-iron grating cl. **C250**
Slope type: Constant invert
Nominal width: 150 mm
Width: 200 mm
Fastening: Screw-fastening

All prices are non-binding and do not include the applicable VAT.
We reserve the right to make technical modifications.

ANRIN SELF-200 drainage channels
from polymer concrete with galvanised mesh grating or slotted ductile-iron grating

Channels only!



Designation	Article	Length cm	Width cm	Height cm	Weight kg	Pc. / Pal.	€/Pc.
SELF-200 Channel 1,0m with perforation DA/OD 160 for vertical outlet	07321001	100	25.0	15.0	14.8	40	103.80
SELF-200 Channel 0,5m with perforation DA/OD 160 for vertical outlet	07321051	50	25.0	15.0	7.1		76.40
SELF-200P Channel 1,0 m with perforation DA/OD 160 for vertical outlet	07324001	100	25.0	10.0	11.5	40	103.80
SELF-200 Sump unit with dirt trap bucket, connection DA/OD 160	07326001	50	25.0	58.5	37.6		208.10
SELF-200 End cap for Channel start and -end	07327100				0.5		28.00
SELF-200P End cap for Channel start and -end	07327400						28.00
SELF-200 End cap with pipe socket DA/OD 160 for Channel end	07328100				1.0		57.20
Foul air trap DA/OD 160	01006610				1.5		54.00
Pipe connection DA/OD 160	01006810				0.2		22.80

Cover gratings for SELF-200



Designation	Article	Length cm	Width cm	Einl.qu cm	Gewicht kg	Pc. / Pal.	€/Pc.
SELF-200 steel mesh grating, galvanised, cl. B125, MW 30 x 25 mm	07324500	100	25.0	1402	5.1		115.40
SELF-200 steel mesh grating, galvanised, cl. B125, MW 30 x 25 mm	07324520	50	25.0	1402	2.6		78.10
SELF-200 Slotted grating ductile-iron GJS, OvalGrip Design, cl. C250	07325500	50	25.0	825	5.3		71.10

* Perforation DA/OD 160 for vertical outlet

Load capacity:
Slope type:
Nominal width:
Width:
Fastening:

Mesh grating cl. **B125**, ductile-iron-slotted grating cl. **C250**
Constant invert
200 mm
250 mm
Screw-fastening

ANRIN SELF drainage system GL-100
made from polymer concrete with galvanised, ductile-iron or mesh grating



Designation	Article	Lenght cm	Width cm	Height cm	Weight kg	Pc. / Pal.	€uro/ Pc.
GL-100 Channel No. 0	07200000	100	13.0	15.0	10.8		65.30
GL-100 Channel No. 0/05	07200005	50	13.0	15.0	8.1		42.60
GL-100 Channel No. 010	07201000	100	13.0	20.0	13.7		65.30
GL-100 Channel No. 080	07200800	100	13.0	8.0	8.9		65.30
GL-100 Channel No. 0100	07203000	100	13.0	10.0	10.6		65.30
GL-100 Channel No. 05	07200500	100	13.0	17.5	12.3		65.30
GL-100 Channel No. 05/0.5	07200550	50	13.0	17.5	6.1		42.60
GL-100 Channel No. 010/0.5	07201050	50	13.0	20.0	6.8		42.60
GL-100 Channel No. 020	07202000	100	13.0	25.0	17.3		65.30
GL-100 Channel No. 020/0.5	07202050	50	13.0	17.5	8.6		42.60
GL-100 Sump unit, with dirt trap bucket, outlet DA/OD 110 with NBR ring and perforations DA/OD 110/160	07206000	50	13.0	56.3	24.0		165.00
GL-100 Steel slotted grating galvanised, cl. A15 , with TwistLock-fastening	07203200	100	12.4	2.1	1.9		27.40
GL-100 Steel slotted grating galvanised, cl. A15 , with TwistLock-fastening	07203220	50	12.4	2.1	1.2		19.30
GL-100 steel mesh grating galvanised, cl. B125 , with TwistLock-fastening	07203300	100	12.4	2.1	3.2		62.40
GL-100 steel mesh grating galvanised, cl. B125 , with TwistLock-fastening	07203320	50	12.4	2.1	1.6		42.00
GL-100 ductile-iron slotted grating, cl. C250 , with TwistLock-fastening	07203500	50	12.4	2.1	3.2		45.50
GL-100 End cap closed							
for Channel No. 0 - 010	07207100						22.80
for Channel No. 20	07208100						22.80
for Channel No. 080	07208800						39.10
GL-100 End cap with Pipe socket							
for Channel No. 0	07207000						39.10
for Channel No. 10	07207200						39.10
for Channel No. 20	07208200						39.10



Load capacity: **A15, B125, C250** according DIN 19580 / EN 1433
Slope type: Stepped invert or Constant invert
Material: Polymer concrete
Nominal width: 100 mm
Width: 130 mm
Fastening: TwistLock-fastening


All prices are non-binding and do not include the applicable VAT.
We reserve the right to make technical modifications.

ANRIN SELF yard sumps
Structural elements around the house



Designation	Article	Lenght cm	Width cm	Height cm	Weight kg	Pc. / Pal.	€uro/ Pc.
SELF Yard sump with galvanised grating with integrated syphon PE-mud bucket and shaped outlet DA/OD 110	07012350	25	25	35	15.4	24	170.80
SELF Yard sump with galv. steel frame and inset ductile-iron grating cl. B125 with integrated syphon PE-mud bucket and shaped outlet DA/OD 110	07012361	25	25	37	19.8	24	241.30
SELF Yard sump with galvanised mesh grating MW 33 x 12 mm with integrated syphon PE-mud bucket and shaped outlet DA/OD 110	07012370	25	25	37	15.8	24	251.80
SELF Yard sump with stainless steel frame and integrated stainless steel longitudinal-bar grating SW = 5 mm with integrated syphon PE-mud bucket and shaped outlet DA/OD 110	07012371	25	25	37	15.8	24	350.30
SELF Yard sump- Attachment box for increasing the height with formed stand pipe connection DA/OD 110	07012900	25	25	25	5.8	24	74.10

ANRIN SELF boot scrapers



Designation	Article	Lenght cm	Width cm	Height cm	Weight kg	Pc. / Pal.	€uro/ Pc.
SELF Boot scraper complete with grating from polymer concrete, with drainage hole and galvanised diamond grating							
Dimensions 60 x 40 cm	07010600	60	40	8	13.3	40	103.20
Dimensions 75 x 50 cm	07010750	75	50	8	21.4	20	134.70

Designation	Article	Length cm	Width cm	Height cm	Weight kg	Pc. / Pal.	Euro/ Pc.
Boot scraper box Nominal dimensions:							
60 x 40 cm	07020100	60	40	8	11.7	40	75.80
75 x 50 cm	07020200	75	50	8	19.7	20	95.00
100 x 50 cm	07020300	100	50	8	22.9	20	114.30

Aluminium grating with needle-felt strips , colour anthracite, rollable, particularly suitable for roofed areas	07021100	60	40	2	2.5		169.00
	07021200	75	50	2	4.0		250.00
	07021300	100	50	2	5.4		331.60







Aluminium grating with rubber strips , colour black, rollable, particularly suitable for wet areas	07021110	60	40	2	2.5		194.70
	07021210	75	50	2	4.0		291.40
	07021310	100	50	2	5.4		385.20

Aluminium grating brushes + rubber strips , colour anthracite, rollable	07021150	60	40	2	2.9		253.00
	07021250	75	50	2	4.7		379.40
	07021350	100	50	2	6.4		499.50

Aluminium grating with brush strips , colour anthracite, rollable,	07021160	60	40	2	2.2		282.10
	07021260	75	50	2	3.5		422.00
	07021360	100	50	2	4.3		558.30

Mesh grating galvanised steel mesh width 9 x 30 mm with strong vertical mesh	07021120	60	40	2	6.0		85.10
	07021220	75	50	2	9.0		128.80
	07021320	100	50	2	12.0		145.70

Diamond grating galvanised steel with strong rod reinforcement	07021140	60	40	2	3.2		46.10
	07021240	75	50	2	4.6		64.20
	07021340	100	50	2	6.2		88.60



Material:

Scraper boxes from polymer concrete,
frame made from tension-free, integrated steel
covering according to choice.

Construction:

Easily cleaned central supports and outlet DA/OD 110

All prices are non-binding and do not include the applicable VAT.
We reserve the right to make technical modifications.



ANRIN
LEADING WATER


ANRIN SPORT
Construction
Elements

Drainage and
edging of
sport facilities

Are you planning a specific sports project or are you involved in tendering for sports facilities?

Send us your query. We will put together a quote specifically for your project as quickly as possible – and we would be delighted to advise you on the technical implementation of drainage and edging for sports facilities.

- 1 Tray channel sport field Wadersloh
- 2 Synthetic turf drainage – sport field, Hahnstrasse (FFM)
- 3 Track drainage with NW 125 slotted channels – sport field, Langenselbold



ANRIN Sport drainage system 125
for sports arenas with raised turf field

Designation	Article	Lenght cm	Width cm	Height cm	Weight kg
Channel 125 A, straight without raised edge	04111000	100	16.0	20.0	16.0
Channel 125 B, curved R = 36.5 m without raised edge	04112000	100	16.0	20.0	16.0
Channel 125 E, straight with raised edge	04113000	100	17.5	24.0	18.0
Channel 125 F, curved with raised edge	04114000	100	17.5	24.0	18.0




Designation	Article	Lenght cm	Width cm	Height cm	Weight kg
Sump unit 125 J without raised edge, with mud bucket and perforations DA/OD 110/160	04117000	50	16.0	58.5	29.0
Sump unit 125 K with raised edge, with mud bucket and perforations DA/OD 110/160	04118000	50	17.5	58.5	29.6
ANRIN Plastic cover PE-HD, white, immovable, straight	04370000	100	16.0	5.0	
ANRIN Plastic cover PE-HD, white, immovable, curved	04371000	100	16.0	5.0	



Prices on request.
We reserve the right to make technical modifications.

ANRIN Sport drainage system 125 slotted channel
for sports arenas with equal height surfaces



NW 125 slotted channels with coatable top and claw grooves
for covering with In-Situ coatings

Designation	Article	Lenght cm	Width cm	Height cm	Weight kg
Channel 125 C.1, straight, one-side coatable, with claw grooves	04112110	100	16.0	20.0	25.0
Channel 125 C.2, curved R = 36.5 m, one-side coatable, with claw grooves	04112210	100	16.0	20.0	24.5
Channel 125 C.3, curved R = 36.5 m, both sides coatable, with claw grooves	04112310	100	16.0	18.7	22.5
Channel 125 C.4, straight, both sides coatable, with claw grooves	04112410	100	16.0	18.7	23.0

NW 125 slotted channels with access opening
top with claw grooves for covering with In-Situ coatings

Channel 125 R.1, straight, one-side coatable, with claw grooves	04112120	100	16.0	20.0	29.0
Channel 125 R.2, curved, R = 36.5 m, one-side coatable, with claw grooves	04112220	100	16.0	20.0	28.0
Channel 125 R.3, curved R = 36.5 m, both sides coatable, with claw grooves	04112320	100	16.0	18.7	25.0
Channel 125 R.4, straight, both sides coatable, with claw grooves	04112420	100	16.0	18.7	24.0
Sump unit 125 L.1, with aluminium-frame and one-side coatable top cover PE-mud bucket and perforations DA/OD 110/160	04119010	50	16.0	63.5	29.9
Sump unit 125 L.3, with aluminium-frame and both sides coatable top cover PE-mud bucket and perforations DA/OD 110/160	04119030	50	16.0	63.5	29.9
ANRIN Plastic cover PE-HD, white, mobile, straight	04373000	100	16.0	5.0	
ANRIN Plastic cover PE-HD, white, mobile, curved R = 36.5 m	04374000	100	16.0	5.0	



ANRIN Sport drainage system 125 slotted channel
for sports arenas with equal height surfaces

NW 125 slotted channels with coatable top without claw grooves
as fitted carpeting for coatings

Designation	Article	Lenght cm	Width cm	Height cm	Weight kg
Channel 125 C.5, straight, one-side coatable, flat top cover	04112510	100	16.0	20.0	26.0
Channel 125 C.6, curved R = 36.5 m, one-side coatable, flat top cover	04112610	100	16.0	20.0	25.5
Channel 125 C.7, curved R = 36.5 m, both sides coatable, flat top cover	04112710	100	16.0	18.7	23.5
Channel 125 C.8, straight, both sides coatable, flat top cover	04112810	100	16.0	18.7	22.5

NW 125 slotted channels with access opening
top without claw grooves as fitted carpeting for coatings

Channel 125 R.5, straight, one-side coatable, flat top cover	04112520	100	16.0	20.0	26.0
Channel 125 R.6, curved, R = 36.5 m, one-side coatable, flat top cover	04112620	100	16.0	20.0	26.0
Channel 125 R.7, curved, R = 36.5 m, both sides coatable, flat top cover	04112720	100	16.0	18.7	24.0
Channel 125 R.8, straight, both sides coatable, flat top cover	04112820	100	16.0	18.7	24.0
Sump unit 125 L.5, with aluminium-frame and one-side coatable top cover PE-mud bucket and perforations DA/OD 110/160	04119050	50	16.0	63.5	29.9
Sump unit 125 L.7, with aluminium-frame and both sides coatable top cover PE-mud bucket and perforations DA/OD 110/160	04119070	50	16.0	63.5	29.9
ANRIN Plastic cover PE-HD, white, mobile, straight	04373000	100	16.0	5.0	
ANRIN Plastic cover PE-HD, white, mobile, curved R = 36.5 m	04374000	100	16.0	5.0	



Prices on request.
We reserve the right to make technical modifications.

ANRIN Sport drainage system tray channel
for sports arenas type C and D



For sports arenas type C and D

Designation	Article	Lenght cm	Width cm	Height cm	Weight kg
Tray channel type H7, straight, with 2 anchors	04211010	100	25.0	7.0	19.0
Tray channel type H7, curved, R = 36.6 m with 2 anchors	04212010	100	25.0	7.0	19.0
Sump unit for tray channel H7, with PE-mud bucket and perforations DA/OD 110, with sealing ring with integrated expansion joints tape	04215000	50	25.0	37.5	11.5
Grating, Compound, cl. B125 , OvalGrip Design SW 8 mm, color grey for insertion in the inlet opening	01004140	50	12.3		1.2

Special design for three-center curves and special radii

Tray channel type H7, straight, with 2 anchors, polygonal, for laying in R= 18.0 m to R= 30.0 m	04205020	50	25.0	7.0	11.0
--	----------	----	------	-----	------

ANRIN Sport drainage system tray channel
for sports arenas type C and D

With claw grooves for sports arenas with synthetic surface

Designation	Article	Length cm	Width cm	Height cm	Weight kg
Tray channel type H7, straight, with 2 anchors model with claw grooves	04211020	100	25.0	7.0	19.0
Tray channel type H7, curved, R = 36.6 m with 2 anchors model with claw grooves	04212020	100	25.0	7.0	19.0
Sump unit for tray channel H7, with PE-mud bucket and perforations DA/OD 110, with sealing ring, with integrated expansion joints tape	04215001	50	25.0	37.5	11.5
Grating, Compound, cl. B125 , OvalGrip Design SW 8 mm, color grey for insertion in the inlet opening	01004140	50	12.3		1.2

Special design for three-center curves and special radii,
model with claw grooves

Tray channel type H7, straight, with 2 anchors, polygonal, for laying in Radii R= 18.0 m to R= 30.0 m model with claw grooves	04205030	50	25.0	7.0	11.0
---	----------	----	------	-----	------



External bordering of running tracks with synthetic surface

Turf edge plate, straight, with 4 anchors, with claw grooves	04204500	100	25.0	6.5	19.0
Turf edge plate, curved, R = 44.1 m, with 4 anchors, with claw grooves	04204600	100	25.0	6.5	19.0

ANRIN Sport
Turf edge plate



Prices on request.
We reserve the right to make technical modifications.

ANRIN Sport drainage system NW 100 synthetic turf
for rectangular synthetic turffields



Designation	Article	Lenght cm	Width cm	Height cm	Weight kg	Pc. / Pal.
Clamp channel NW 100, with drain openings in the clamp slot, with grating cl. A and TwistLock-fastening incl. clamp set	04401001	100	18.8	20.0	15.4	25
Mitre cut at camp channel and grating for 90° corners Req. 8 pieces / field	01307600					
Sump unit for clamp channel NW 100 with PE-mud bucket and perforations DA/OD 110 and 160, with grating cl. A with fastening incl. clamp set	04403001	50				

ANRIN Sport
drainage system NW 125 synthetic turf
for synthetic turffields in sports arenas




Designation	Article	Lenght cm	Width cm	Height cm	Weight kg
Clamp channel NW 125, straight with drain openings in the clamp slot, 4 cm raised clamp side, incl. clamp set	04411000	100	23.0	24.0	27.1
Clamp channel NW 125, curved R = 36.5 m, with drain openings in the clamp slot, 4 cm raised clamp side, incl. clamp set	04412000	100	23.0	24.0	27.1
Sump unit for clamp channel NW 125, with mud bucket and perforation DA/OD 110, incl. clamp set	04413000	50	23.0	62.5	35.9

Accessories					
ANRIN Plastic cover PE-HD, white, straight, immovable	04370000	100	16.0	5.0	
ANRIN Plastic cover PE-HD, white, curved R = 36.5 m immovable	04371000	100	16.0	5.0	

ANRIN Sport Clamp stone for bordering synthetic turf fields
in combination with block paving, kerbings or channels

Designation	Article	Lenght cm	Width cm	Height cm	Weight kg
Clamp stone with 5 cm concrete edge Clamp side lowered by 13 mm incl. clamp set	04435003	100	10.0	20.0	21.1
Mitre cut at clamp stone for 90° corners Req. 8 pieces / field	01307600				



ANRIN Sport Clamp rail for bordering synthetic turf fields
in combination with block paving, kerbings or channels


Designation	Article	Lenght cm	Width cm	Height cm	Weight kg
Clamp rail galvanised steel, with 4 anchors, incl. clamp set	04436001	200	3.2	5.5	7.0
Mitre cut at clamp rail for 90° corners Req. 8 pieces / field	01307600				



ANRIN SPORT Clamp set
for clamping synthetic turf in the ANRIN SPORT clamping system
consisting of plastic wedges and U-rails.
For each meter of the clamping system, 4 plastic wedges and 2 U-rails are required.

Prices on request.
We reserve the right to make technical modifications.

ANRIN Sport soft kerbings with white rubber profile
for bordering running tracks, playing fields and long jump pits



Designation	Article	Lenght cm	Width cm	Height cm	Weight kg
Soft kerbing, white rubber profile	04521000	100	6.0	40.0	21.3
Length compensation, 50 cm	04521100	50	6.0	40.0	11.1
Corner piece leg length (internal) 25 cm	04521200	25	6.0	40.0	12.1
Soft kerbing, white rubber profile	04522000	100	6.0	30.0	18.8
Length compensation, 50 cm	04522100	50	6.0	30.0	10.0
Corner piece leg length (internal) 25 cm	04522200	25	6.0	30.0	11.0
Soft kerbing, white rubber profile	04523000	100	6.0	25.0	17.3
Soft kerbing, white rubber profile	04524000	100	6.0	20.0	15.9
Soft kerbing, white rubber profile	04526000	100	5.0	25.0	14.2
Soft kerbing, white rubber profile	04527000	100	5.0	20.0	12.5
Mitre cut for 90° corners	01307600				


ANRIN Sport soft kerbings with black rubber profile
for bordering running tracks, playing fields and long jump pits

Designation	Article	Lenght cm	Width cm	Height cm	Weight kg
Soft kerbing, black rubber profile	04501000	100	6.0	40.0	21.3
Length compensation, 50 cm	04501100	50	6.0	40.0	11.1
Corner piece leg length (internal) 25 cm	04501200	25	6.0	40.0	12.1
Soft kerbing, black rubber profile	04502000	100	6.0	30.0	18.8
Length compensation, 50 cm	04502100	50	6.0	30.0	10.0
Corner piece leg length (internal) 25 cm	04502200	25	6.0	30.0	11.0
Soft kerbing, black rubber profile	04503000	100	6.0	25.0	17.3
Soft kerbing, black rubber profile	04504000	100	6.0	20.0	15.9
Soft kerbing, black rubber profile	04506000	100	5.0	25.0	14.2
Soft kerbing, black rubber profile	04507000	100	5.0	20.0	12.5
Soft kerbing, black rubber profile	04509500	100	10.0	25.0	19.5
Soft kerbing, black rubber profile	04508000	100	10.0	40.0	33.8
Mitre cut for 90° corners	01307600				



Prices on request.
We reserve the right to make technical modifications.

ANRIN Sport Sand trap channel
for the collection of sand from long jump pits



Designation	Article	Lenght cm	Width cm	Height cm	Weight kg
Sand trap channel, with steel edge with rubber mat on steel grating	04571000	100	50.0	14.0	43.0
Length compensation, 112 cm	04572000	112	50.0	14.0	48.0
Length compensation, 67 cm	04571670	67	50.0	14.0	
End cap with steel edge	04573000		50.0	14.0	2.9

ANRIN Sport
Spot intake
point drainage in kerbstone bordering



Designation	Article	Lenght cm	Width cm	Height cm	Weight kg
Spot intake, sigle-side inlet, with PE-mud bucket, with perforations DA/OD 110 polymer concrete cover, matching the concrete block	04555000	50	15.0	35.0	18.0



Spot intake, two-side inlet, with PE-mud bucket, with perforations DA/OD 110 polymer concrete cover, matching the concrete block	04565000	50	15.0	35.0	18.0
---	----------	----	------	------	------

ANRIN Sport cable distribution shaft
for the permanent and temporary wiring of sports facilities


Designation	Article	Lenght cm	Width cm	Height cm	Weight kg
Cable distribution shaft with steel frame, perforations DA/OD 110/160 on all sides	04611000	60.0	60.0	60.0	57.0
Cover galvanised steel, coatable on-site	04613010	60.0	60.0		
Cover galvanised steel, checker plate	04613020	60.0	60.0		



Prices on request.
We reserve the right to make technical modifications.


A15

with road concrete
or concrete sheets
or block paving




A15

with cast asphalt




B125

with road concrete
or concrete sheets
or block paving




B125

with cast asphalt




C250

with road concrete
or concrete sheets
or block paving



C250


with cast asphalt



D400

E600


with road concrete
or concrete sheets
or block paving



D400,


E600

with cast asphalt




F900

with road concrete
or concrete sheets
or block paving



F900

with cast asphalt



1. Cast road concrete
2. Base
3. Concrete cladding of the channel body
4. Sub-base, natural soil
5. Prefabricated concrete sheets or stone systems

6. Paving bed
7. Wearing course
8. Bonding course
9. Bitumen base
- FDS = joint sealing system

1. Scope of terms and conditions

Our deliveries, services and offers are provided exclusively on the basis of the following terms and conditions. These conditions therefore also apply to all future terms and conditions, including where they have not been again expressly agreed. These terms and conditions are deemed to have been accepted, at the latest, upon receipt of the goods or services. Counterconfirmations on the part of our contract partners which refer to their own general terms and conditions are hereby rejected, and are also inapplicable regardless of whether referred to in writing with orders or deliveries. Deviations from these terms and conditions only apply where confirmed by us in writing.

2. Offer and conclusion of contract

Our offers are subject to alteration and are non-binding. Declarations of acceptance and all orders must be confirmed in writing or by telex to be legally valid. This also applies to supplements, amendments or ancillary agreements or the verbal undertakings of our employees.

3. Prices and terms of payment

(1) Unless otherwise specified in the confirmation of order, our prices apply „ex-factory“ excluding packaging, which will be charged separately. We reserve the right to reasonably increase our prices where, following conclusion of the contract, cost increases are incurred, particularly as a consequence of collective pay agreements or material price increases. Evidence of such increases will be provided to the customer upon request.
(2) Statutory Value Added Tax is not included in our prices. This will be shown separately in the invoice at the statutory rate applicable on the date of invoice.
(3) Discount deductions require a separate, written agreement.
(4) Unless otherwise specified in the confirmation of order, the purchase price is payable net (without deductions) within 30 days of the invoice date. Wheresoever the customer defaults on payment, we are entitled to demand interest of 4% p.a. above the respective discount rate of the German Bundesbank. Insofar as we are able to supply evidence of greater damages incurred due to default, we are entitled to assert a claim for such. The customer is, however, entitled to supply us with evidence demonstrating that no damages or significantly lower damages were incurred by ourselves as a result of the default on payment.
(5) The customer is not entitled to deny, withhold or set-off payments on the basis of any counterclaims, unless such counterclaims are judicially non-appealable, uncontested or have been acknowledged by us.

4. Delivery and service times

(1) The dates and deadlines stated by us are non-binding insofar as not otherwise expressly agreed in writing.
(2) Wheresoever we are prevented from the timely fulfillment of our obligations as a result of force majeure or other unforeseeable, extraordinary circumstances occurring in the absence of fault, for example, difficulties in obtaining materials, stoppages, strike, shut-out, shortage of transport facilities, official actions, difficulties with energy supplies etc. – including where these occur at our suppliers – the delivery date shall be extended accordingly. Should the stated circumstances make delivery or provision of services impossible or unreasonable, we shall be released of our delivery obligations. We shall inform the customer as quickly as possible of the beginning and end of any such obstructions. The customer may request that we declare, within a period of two weeks, whether we wish to withdraw from the agreement or effect delivery within a reasonable period.
(3) In the event that we default on delivery for reasons occasioned by ourselves, liability for damages due to ordinary negligence shall be precluded.
(4) Wheresoever, subsequent to us defaulting on delivery, the customer grants us a reasonable extension for delivery under threat of rejection, the customer shall be entitled to withdraw from the contract in the event that we fail to deliver by the said extended delivery date; claims for compensation due to non-performance for the amount of foreseeable damage may only be asserted by the customer where the default is based on wrongful intention or gross negligence; in remainder, liability for compensation shall be limited to 50% of actual damages incurred.
(5) Restrictions to liability stipulated in Ss. 3 and 4 above do not apply insofar as a fixed date of delivery has been agreed commercially, or where, in the event of default occasioned by ourselves, the customer is able to assert that its interests in performance of the contract have lapsed.
(6) Observance of our delivery obligations is conditional upon the due and proper fulfillment of customer obligations.
(7) Should the customer default in accepting goods or otherwise infringe his obligation to co-operate, we are entitled to claim damages incurred by ourselves, including any additional expenses. In such cases, the risk of accidental destruction or accidental deterioration of the goods passes to the customer at the point in time in which it defaults in acceptance.
(8) We are entitled to make partial deliveries or render partial services at all times. The customer is obliged to pay separately according to our terms of payment for partial deliveries and partial services that are charged separately by us.

5. Transfer of risk, shipping, insurance

(1) Unless otherwise stated in the confirmation of order, delivery „ex-factory“ is agreed.
(2) If the customer wishes, we will arrange for the delivery to

be covered by a transport insurance policy; all associated costs incurred for such shall be borne by the customer.
(3) Where freight-paid delivery is agreed, this shall be executed with transport facilities determined by us, and excludes unloading. This is further subject to the requirement that stable roads exist which can support heavy freight vehicles. Waiting times and unloading times of more than 30 minutes per 5 t will be charged separately to the customer.

6. Warranty for defects

(1) The customer will examine the received goods without delay to determine defects, condition and guaranteed properties and is to report obvious defects within one week in writing. Defects which are not revealed despite a careful examination within this period must be reported without delay and in writing immediately upon their discovery. An opportunity to establish the defect on site is to be extended to ourselves.
(2) Should any defects for which we are responsible be ascertained in the goods, at our discretion, we are entitled to remedy such defects or replace the delivery. If defects are remedied, we shall bear all costs for materials, transport and labor; however, only half the costs for installation and assembly. In the event that these costs are increased as a result of the goods being moved to a place other than the place of fulfillment, such costs shall not be borne by us.
(3) Should we be unwilling or unable to effect remedy of the defect/replacement delivery, particularly where such action is delayed beyond reasonable periods for reasons occasioned by us, or wheresoever the remedy of defect/replacement delivery fails for other reasons, at its own discretion, the customer is entitled to claim a reduction in price or, provided that construction work is not the subject of the warranty, to withdraw from the agreement.
(4) Insofar as not otherwise specified below, further claims on the part of the customer – regardless of legal basis – are precluded. Consequently, we do not accept liability for damages not caused to the delivery item itself. In particular, we do not accept liability for loss of profit or other economic loss on the part of the customer.
(5) The above exemption from liability does not apply insofar as the cause of damages originates from wrongful intention or gross negligence, or where the customer claims damages for non-performance due to the lack of a guaranteed property in accordance with Ss. 463, 480 (2) of the German Civil Code (BGB).
(6) Insofar as we negligently infringe a substantial obligation of the agreement, we will be liable to compensate foreseeable damage.
(7) The period of warranty is 24 months effective from the transfer of risk. This period is a term of limitation and also applies to claims for compensation for consequential damages, insofar as no claims arising from tortious acts are asserted.

7. Overall liability

(1) Liability for damages extending beyond that stipulated in S. 6 (4) to (6) is precluded regardless of the legal nature of the asserted claim.
(2) The provision of (1) above does not apply to claims made under Ss. 1, 4 of the German Product Liability Act (Produkthaftungsgesetz). This also applies with respect to initial incapacity or justifiable impossibility.
(3) Insofar as liability on our part is precluded or limited, this will also apply with respect to the personal liability of our employees in all positions, representatives and vicarious agents.
(4) The limitation of claims arising from manufacturer's liability in accordance with S. 823 BGB is dependent on S. 6 (7), regardless of whom such claims are asserted against.

8. Retention of title

(1) We reserve title to the goods delivered by us until all payments arising from the business relationship with the customer have been received. Insofar as we agree with the customer that payment of the debt may be in the form of check/bill of exchange, this reservation also persists until redemption of the bill of exchange accepted by ourselves has been effected by the customer, and is not discharged through the credit entry effected by ourselves for receipt of the check.
(2) In the event of conduct contrary to the terms of the contract on the part of the customer, in particular with respect to default on payments, we are entitled to recover the delivered goods. Recovery of the goods by us does not represent a withdrawal from the agreement unless we expressly declare such in writing. Levy of execution (seizure) of the goods by us shall constitute a withdrawal from the agreement in all cases. We are entitled to realize the value of the goods following their recovery, whereby – subject to an appropriate deduction for realization costs – the proceeds from such realization will be credited to accounts payable by the customer.
(3) The customer is obliged to handle the goods with care. In particular, at its own expense, the customer is obliged to adequately insure the goods at value as new against fire, water damage and theft. In the event that maintenance and inspection work is necessary, the customer must conduct such work promptly at its own expense.
(4) The customer must notify us without delay in writing of any levy of execution (seizure) or other actions by third parties in order that we may institute proceedings under S. 771 of the German rules of civil procedure (ZPO). Wheresoever the third party is unable to reimburse us for the judicial and extrajudicial costs of legal proceedings in accordance with S. 771 ZPO, the customer will be liable for any loss incurred on our part.
(5) The customer is entitled to resell the delivered goods in the ordinary course of business; however, it hereby assigns to us all accounts receivable to the total value of the invoice (including VAT) accruing to it from sales to its customers or

third parties, and regardless of whether the goods have been sold without or following reprocessing. The customer remains entitled to enforce collection of such accounts receivable following this assignment, whereby our authority to collect the accounts receivable remains without prejudice. However, we undertake to refrain from collection of the accounts receivable insofar as the customer fulfills its payment obligations from the earnings received, is not in default on payments and, in particular, insofar as no application for the institution of bankruptcy or settlement proceedings is submitted, or suspension of payments effected. Should such a case arise, we are entitled to require that the customer notifies us of the assigned account receivable and its commensurate debtor, provides all information necessary to facilitate collection, submits all associated documents, and informs the debtors (third parties) of the assignment.
(6) Any reprocessing or reworking of goods delivered by us on the part of the customer is continually conducted on our behalf. Wheresoever the goods are processed with other objects for which we do not hold title, we shall acquire co-ownership of the new product in a ratio of the value of the goods for which we hold title to that of the other processed objects at the time of reprocessing. In remainder, the same applies to the product of such processing as is the case for goods delivered under reservation of title.
(7) If the goods are indivisibly combined with other objects for which we do not hold title, we shall acquire co-ownership of the new product in a ratio of the value of the object of sale to that of the other combined objects at the time of combination. If combination is conducted in a manner by which the product of the customer is regarded as the main product, it is hereby agreed that the customer shall assign proportionate co-ownership to us. The customer will preserve the resulting sole or co-ownership on our behalf.
(8) In order to secure our accounts receivable against it, the customer shall also assign to us any accounts receivable acquired against a third party as a result of combining the goods with land.
(9) We undertake to release, at the request of the customer, securities to which we are entitled, insofar as the value of our securities exceeds the accounts receivable to be secured by more than 20%. The choice of the released securities is incumbent upon ourselves.
9. Place of fulfillment, legal venue, partial invalidity, applicable law. The place of fulfillment for all of our services is Anröchte. Legal venue for all disputes arising directly or indirectly from the contractual relationship is Lippstadt. Wheresoever any provision of these terms and conditions, or any provision within the scope of other agreements, is or becomes invalid, this shall not prejudice the validity of all remaining provisions or agreements. In the event that any individual provisions are invalid, the parties undertake to agree an alternative provision by mutual consent, which most closely meets the economic intention of the intended provision. German law applies exclusively.

ANRIN GmbH

Siemensstraße 1, D - 59609 Anröchte

Issue 01.04.2012



ANRIN GmbH
Siemensstr. 1
59609 Anröchte
Germany

+49 (0) 29 47.97 81-0
www.anrin.com
info@anrin.com